



### MA-WA82220-DBDP14

## 698-960 MHz & 1700-2700 MHz Stadium Dual Band & Dual Pol Directional Antenna

MARS new DUAL BAND and DUAL POL antenna specially **designed for arenas and stadiums** that have to supply high capacity and reliable wireless data.

MARS MA-WA82220-DBDP14 provides solutions for services such as LTE, Cellular (2G, 2.5G and 3G), Wi-Fi and WiMAX applications.

The antenna is PIM certified, thus making it suitable for all multi-carrier systems.

#### Additional Features:

- Efficient and stable performance with 12-13 dBi of gain.
- UV protected radome suitable for harsh environment installations
- Durable construction
- · Easy mounting allowing Az/El adjustment
- · Aesthetic design
- · Weatherized and durable
- Wind survival rating of 200 km/h



# Specially designed for Stadiums

# **Specifications**

	cal	

Liccificat				
Frequency range		698-960 MHz	1700-2700 MHz	
Gain, typ.	V-pol H-pol	12 dBi 13 dBi	13 dBi 13 dBi	
VSWR, max.		2.0 : 1		
Polarization	Dual Pol	Vertical & Horizontal		
Port to Port Isolation, min.		-22 dB	-37 dB	
3dB Beam-Width, Azimuth, typ.		35°	35°	
3dB Beam-Width, Elevation, typ.		35°	35°	
Front to Back Ratio, min.		-22 dB		
PIM, 3 <sup>rd</sup> order, 2X20W		-150 dBc		
Input power, max.		50 Watt		
Impedance		50 Ohm		

### Mechanical

Dimensions (HxWxD)	800 x 600 x 110 mm	
Connector	2 x N-type Female	
Weight	6 Kg.	
Mounting	See Ordering Options	
Radome	UV Protected Plastic	
Back Plane	Aluminum protected through chemical passivation.	

#### Environmental

Operating Temperature Bongs	-55°C to +65°C
Operating Temperature Range	-55°C 10 +65°C
Vibration	According to IEC 60721-3-4
Wind Load	200 Km/h (Survival)
Flammability	UL94
Water Proofing	IP-67
Humidity	ETS 300 019-1-4,EN 302 085 (Annex A.1.1)
Salt Fog	According to IEC 68-2-11

# **Ordering Options**

MA-WA82220-DBDP14	Antenna 2 x N-type Female connectors Suited for MNT-25 mount
MA-WA82220-DBDP14B	Antenna 2 x N-type Female connectors with MNT-25 mount

MARS Antennas & RF Systems proprietary information

MARS reserves the right to make technical changes or modifications to any of its products and specifications without prior notice and without implementing such changes to prior supplied products. Product images are representative and indicative only. Warranty terms and general conditions of sale are applicable on any purchase of any product, available on MARS website.

Tel: +972-3-5599661 • Fax: +972-3-5599677 • e-mail: mars@marsant.co.il • web: www.mars-antennas.com