

# Mini-focus X-ray module

XWFR Series

01.165.02|31-1



## FEATURES

- Equip X-ray tube of focus dimensions 100 $\mu$ m
- User-friendly operation
- Continuous operation is available.

## SUMMARY

XWFR series is the 2-unit type X-ray module with high-stability power supply and Mini-focus X-ray tube. Achieve high-contrast X-ray image by high power X-ray and using Beryllium window. And, achieve clear X-ray image even zooming in, because focal distance is 100 $\mu$ m.

## LINEUP

|  |                 |                                  |
|--|-----------------|----------------------------------|
| Anode voltage                                      | MAX             | 60kV                             |
|  | MIN             | 6kV                              |
| Beam current                                       |                 | 1mA                              |
| Max Power  |                 | 60W                              |
| Focal spot size                                    |                 | 100 $\mu$ m                      |
| Radiation angle                                    |                 | 20°                              |
| Window material                                    |                 | Beryllium                        |
| Operation  |                 | Continuous                       |
| Dimension<br>WxDxH<br><small>inch<br/>(mm)</small> | Controller unit | 8.35×12.99×5.51<br>(212×330×140) |
|  | X-ray unit      | 5.12×10.75×6.97<br>(130×273×177) |
| Weight<br>(kg approx)                              | Controller unit | 10                               |
|  | X-ray unit      | 6                                |
| Model  |                 | XWFR60-60                        |

## SPECIFICATIONS

|                       |  |
|-----------------------|--|
| <b>Input voltage</b>  | 100VAC to 120VAC 50/60Hz single phase<br>200VAC to 240VAC 50/60Hz single phase (-L(200V)option)  |
| <b>Output control</b> | Voltage<br>Local : 10-turn potentiometer on front panel<br>Remote : External control voltage 0 to 10Vdc<br>(Input impedance more than 1M $\Omega$ )<br>or by external 5k $\Omega$ potentiometer<br>Current<br>Local : 10-turn potentiometer on front panel<br>Remote : External control voltage 0 to 10Vdc<br>(Input impedance more than 1M $\Omega$ )<br>or by external 5k $\Omega$ potentiometer |
| <b>Display</b>        | Output voltage : 3½-digit digital meter<br>Output current : 3½-digit digital meter<br>LED display of the status of X-ray ON/OFF, STNDBY, INTERLOCK and AGING   |
| <b>Monitor output</b> | Output voltage monitor : 10V/Maximum output voltage<br>(Output impedance 1k $\Omega$ )<br>Output current monitor : 10V/Maximum output current<br>(Output impedance 1k $\Omega$ )   |

|                        |  |
|------------------------|--|
| <b>Protections</b>     | Over voltage protection<br>Over current protection<br>Protection against output short-circuit and arc discharge<br>Filament protection<br>Blackout protection<br>Over temperature protection |
| <b>Other functions</b> | Remote switch ON/OFF<br>Interlock by door switch<br>Output status signal output  |
| <b>Operating temp.</b> | 0 to +40°C   |
| <b>Storage temp.</b>   | 0 to +50°C   |
| <b>Humidity</b>        | 30% to 80%RH (no condensation)   |
| <b>Accessories</b>     | AC line input cable 2.5m (1)<br>Shielded HV output cable 2.5m (1)<br>Instruction manual (1)  |

**-L(200V)** 200VAC to 240VAC 50/60Hz single phase input

\*When ordering, suffix the above option number to the model number.

#### Warranty

We warrant that products contained in this catalog (hereinafter, the "Products") are free from defects in material and workmanship under normal use for a period of one (1) year from the date of shipment thereof. However, the warranty period for X-ray detectors and X-ray source shall be either one (1) year from the date of shipment or 1,000 hours, whichever shorter. The above warranty shall not apply to any Product which, at our sole judgment, has been: i) Repaired or altered by persons unauthorized by us; or ii) Connected, installed, adjusted or used otherwise than in accordance with the instructions furnished by us (including being used in an inappropriate installation environment, such as in corrosive gas, high temperature and humidity). We are not liable for any loss, damage or failure of the Products after the shipment thereof caused by external factors such as disasters. If any Product is showed to be defective as satisfactory to us, we, at our sole discretion, repair or replace such defective Products at no cost to the purchaser. We assume no liability to the purchaser or any third party for special, incidental, consequential, or other damages resulting from a breach of the foregoing warranty. This warranty excludes any and all other warranties not set forth herein, express or implied, including without limitation the implied warranties of merchantability or fitness for a particular purpose. The Products are not designed and produced for such applications as requiring extremely high reliability and safety, or involving human lives (such as nuclear power, aerospace, social infrastructure facility, medical equipment, etc.). The use under such environment is not covered by this warranty and may require additional design and manufacturing processes. Regarding RoHS compliance, Matsusada Precision Inc. does not intentionally use objectionable substances in the products listed within this catalog. Matsusada Precision Inc. manufactures products using components which, according to our suppliers, are "RoHS compliant parts". However, Matsusada Precision does not analyze each and every unit to confirm. Therefore, there may be some customized products which do not comply to RoHS. Please contact your nearby sales office for confirmation.



## Matsusada Precision Inc.

For products [www.matsusada.com/product](http://www.matsusada.com/product) For contact [www.matsusada.com/contact](http://www.matsusada.com/contact)

**San Jose Office** : 2570 N.First Street Suite 200 San Jose, CA 95131  
Tel: +1-408-273-4573 Fax: +1-408-273-4673  
**New York Office** : 80 Orville Drive Suite 100 Bohemia, NY 11716  
Tel: +1-631-244-1407 Fax: +1-631-244-1496

**Dallas Office** : 5430 LBJ Freeway, Suite 1200 Dallas, TX 75240  
Tel: +1-972-663-9336 Fax: +1-972-663-9337  
**Boston Office** : 859 Willard St. One Adams Place, Suite 418 Quincy, MA 02169  
Tel: +1-617-663-5711 Fax: +1-617-663-5331

**International Office** : Osaka-City, Osaka Japan  
Tel: +81-6-6150-5088 Fax: +81-6-6150-5089  
**Headquarters** : 745 Aoji-cho Kusatsu Shiga 525-0041 Japan  
Tel: +81-77-561-2111 Fax: +81-77-561-2112