

OPEN TRANSFER SWITCHES SPECIFICATIONS TABLE

Model			XFF3011	XFF3021	XFF3041	XFF3061	
Rated voltage (Volt 50/60Hz)			AC600V DC125V	AC600V DC125V	AC600V DC125V	AC600V DC125V	
Rated current (Amp.)			100	200	400	600	
Number of poles			3 / 4	3 / 4	3 / 4	3 / 4	
Control Voltage (VAC)			120 / 220	120 / 220	120 / 220	120 / 220	
Short time withstand capacity (kA)	Peak		12	12	12	12	
	rms 1 sec		5	5	5	5	
Operating time	Opening time (Sec.)		0.06	0.06	0.06	0.06	
	Change over time (Sec.)		0.08	0.08	0.08	0.08	
Operating current (Amp.)	AC100/110V		6	6	6	6	
	AC200/220V		3	3	3	3	
	DC100/110V		6	6	6	6	
Mechanical Endurance			50000	50000	50000	50000	
Electrical Endurance			10000	10000	10000	10000	
Switching frequency (times per hour)			150	150	150	150	
Installation	Type	Drawout		N/A	N/A	N/A	N/A
		Fixed		Available	Available	Available	Available
	Dimensions (mm)	Drawout	3 Pole	N/A	N/A	N/A	N/A
			4 Pole	N/A	N/A	N/A	N/A
		Fixed	3 Pole	290 x 270 x 140	290 x 270 x 140	290 x 270 x 140	290 x 270 x 140
			4 Pole	350 x 270 x 140	350 x 270 x 140	350 x 270 x 140	350 x 270 x 140
	Weight (Kgs)	Drawout	3 Pole				
			4 Pole				
Fixed		3 Pole					
		4 Pole					
Controller			Optional	Optional	Optional	Optional	