

SPECIFICATIONS TABLE

Click to see the installation manual



Miami Breaker Type		REF	RHE	RCE	RFJ	RJL	RLL	RKM	RHP	RHR
Replaces ITE* Type		EF	HE	CE	FJ	JL	LL	KM	HP	HR
Number of Poles		2/3	3	3	3	3	3	3	3	3
Current Range		3 - 150	10 - 150	10 - 100	70 - 250	70 - 400	450 - 600	600 - 800	600 - 1600	1800 - 2000
Interrupting Ratings (kA)	240 V _{AC}	18	65	200	22	42	42	42	65	65
	480 V _{AC}	14	25	200	18	30	30	30	50	50
	600 V _{AC}	14	18	100	14	22	22	22	42	42
	250 V _{DC}	10	10	-	10	10	10	20	-	-
Trip Unit	Thermal	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed	Fixed
	Magnetic	Fixed	Fixed	Fixed	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable	Adjustable
Magnetic Only Molded Case Switch		●	●		●	●	●	●	●	●
Accessories	Shunt Trip	●	●	●	●	●	●	●	●	●
	U.V.R.	●	●	●	●	●	●	●	●	●
	Alarm Switch	●	●	●	●	●	●	●	●	●
	Aux. Switch	●	●	●	●	●	●	●	●	●
	Mech. Interlock	●	●	●	●	●	●	●	●	●
Motor Operator					●	●	●	●	●	
Dimensions (In)	Height	6	6	9	10	11	11	15 1/2	15 1/2	15 1/2
	Width (2P)	3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	Width (3P)	4 1/2	4 1/2	4 1/2	4 1/2	9	9	9	9	9
	Depth	3 1/2	3 1/2	4 5/16	4 1/16	4 1/16	4 1/16	4 1/16	4 3/4	4 3/4
Weight (Lb)	2 Poles	3	N/A	N/A	N/A	N/A	N/A	N/A	N/A	N/A
	3 Poles	4	4	7	9	19	22	41	58	58
List Price		**	**	**	**	\$ 3,550	\$ 4,928	\$ 6,648	\$ 17,365	\$ 19,445

* ITE is a registered trademark of Siemens Energy & Automation, Inc. ** Call Miami Breaker N/A Not Applicable