

Indoor Mono Tube Fire Resistant Cable - Multimode

Product Details:

A fire resistant mono tube cable featuring heat resistant Mica tape, glass yarns and an LSZH jacket making it suitable for use in applications such as fire alarm systems, requiring up to 120 minutes of fire resistance in accordance with IEC 60331-25.

Features and Benefits:

- Fire resistant to IEC 60331-25 @ 750°C 120 minutes
- Heat resistant Mica tape
- Red LSZH UV resistant jacket
- Aramid glass yarns provide protection and strength
- Mono tube gel filled construction



Physical Characteristics:

Number of Fibres	6		12	
Number of Fibres per Tube	up to 12			
Number of Elements	1			
Tube/Filler Diameter	2.8mm			
Nominal Cable Diameter	75mm			
Nominal Cable Weight	60kg/km			
Max. Tensile Strength	2.0kN			
Max. Crush Resistance	2.5kN/100mm (Long Term)			
Max. Impact	10 Joules			
Min. Bending Radius	15 x cable OD Installation		10 x cable OD Long term	
Temperature Range	Storage: -40° to 70°C	Installation: -5° to 50°C	Operation: -30° to 70°C	
Waterblocking	Thixotropic Gel filled tube			
Fire Protection Material	Mica Tape			
Rodent Protection	Glass Yarns			
Outer Sheath	Material: UV Resistant LSZH. Colour: Red			
Flame Retardant	IEC 60332-1			
Fire Retardant	IEC 60332-3-24			
Fire Resistance	IEC 60331-25 120 minutes @ 750°C Max Attenuation 0.5dB			

Identification:

Fibre & Buffer Colour Code Chart

No.	1	2	3	4	5	6	7	8	9	10	11	12
Colour	blue	orange	green	brown	grey	white	red	black	yellow	violet	pink	aqua

Fillers are either natural (opaque) or black, jelly filled tubes (with no fibres) are also used.

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.

Optical Characteristics - Multimode Graded Index:

Compliant with the following standards: ISO/IEC 11801, ITU-T G.651.1	
Optical Properties	
Fibre Type	OM3
IEC Standard	11801
Core Diameter	50um
Cladding Diameter	125um
Buffer Diameter	242um
Max. Attenuation of Cable	
@ 850nm	2.8dB/km
@ 1300nm	0.8dB/km

Ordering Information:

Number of Cores	OM3
6	CAB-MT-06-MM3FR
12	CAB-MT-12-MM3FR

In support of our policy of continuous product improvement we reserve the right to change materials and specifications without notice. Drawings, where used, are not to scale. All dimensions are in millimetres and sizes given are approximate. Where possible, technical MSDS data sheets are made available on the website. All products should be installed and used in accordance with manufacturer's instructions provided. Warning: products may be the subject of registered designs and patents. Refer to website for terms and conditions on warranty.