

Thyristor-Diode Module, 320 Amps

Features

- Improved glass passivation for high reliability
- Exceptional stability at high temperatures
- High di/dt and dv/dt capabilities
- Low thermal resistance




Voltage Ratings ($T_A = 25^\circ\text{C}$, unless otherwise noted)					
Type number	Voltage Code	V_{RRM} , Maximum repetitive peak reverse voltage (V)	V_{RSM} , Maximum non-repetitive peak reverse voltage (V)	V_{DRM} , Maximum repetitive peak off-state voltage (V)	I_{RRM} , Maximum reverse leakage current @ T_{JMAX} (mA)
NTD323	60	600	700	600	max. 90
	80	800	900	800	
	100	1000	1100	1000	
	120	1200	1300	1200	
	140	1400	1500	1400	
	160	1600	1700	1600	
	180	1800	1900	1800	

Electrical Characteristics ($T_A = 25^\circ\text{C}$ unless otherwise noted)			
Parameter	Symbol	Values	Units
Maximum average forward current @ $T_J = 85^\circ\text{C}$	$I_{T(AV)}$	320	A
Maximum average RMS forward current	$I_{T(RMS)}$	500	A
Maximum non-repetitive surge current	I_{TSM}	9500	A
Maximum I^2t for fusing	I^2t	451250	A^2s
Forward voltage drop	V_{TM}	max. 1.45	V
Critical rate of rise of on-state current	di/dt	max. 130	$\text{A}/\mu\text{s}$
Critical rate of rise of off-state voltage	dv/dt	max. 1000	$\text{V}/\mu\text{s}$
Gate current required to trigger	I_{GT}	min. 150	mA
Gate voltage required to trigger	V_{GT}	min. 2	V
Maximum holding current	I_H	150	mA
Maximum latching current	I_L	300	mA
Isolation voltage	V_{ISO}	3000	V

Thermal & Mechanical Specifications ($T_A = 25^\circ\text{C}$ unless otherwise noted)			
Parameter	Symbol	Values	Units
Operating junction temperature range	T_J	-40 to +130	$^\circ\text{C}$
Storage temperature	T_{stg}	-40 to +125	$^\circ\text{C}$
Thermal resistance, junction to case	$R_{th(jc)}$	0.09	$^\circ\text{C}/\text{W}$
Mounting torque	to heatsink	$5 \pm 15\%$	Nm
	to terminals	$8 \pm 15\%$	
Weight	W	620	g

Package Outline

(All dimensions in mm)



Circuit Configuration

Circuit Description	Configuration Code	Circuit Drawing
Series Connection (doubler circuit)	N	<p>The circuit drawing for the Series Connection (doubler circuit) shows two diodes connected in series. Terminal 1 is the AC input. Terminal 2 is the positive output (+). Terminal 3 is the negative output (-). Terminal 4 is Ground (G). Terminal 5 is the Cathode (K). Terminal 6 is the Anode (A).</p>
Common Anode	A	<p>The circuit drawing for the Common Anode configuration shows two diodes with their anodes connected to terminal 1. The cathodes are connected to terminals 2 and 3. Terminal 4 is Ground (G). Terminal 5 is the Cathode (K). Terminal 6 is the Anode (A).</p>



Ordering Table

<i>NTD</i>	<i>323</i>	<i>N</i>	<i>160</i>
1	2	3	4

1 – Power Module

- > DD = Diode-Diode
- > TD = Thyristor-Diode
- > TT = Thyristor-Thyristor

2 – Current Rating = $I_{T(AV)}$

3 – Circuit Configuration (see Table)

4 – Voltage Code (see Voltage Ratings table)