

## Thyristor-Thyristor Module, 460 Amps

**Features**

- Improved glass passivation for high reliability
- Exceptional stability at high temperatures
- High di/dt and dv/dt capabilities
- Low thermal resistance


| Voltage Ratings ( $T_A = 25^\circ\text{C}$ , unless otherwise noted) |              |                                                            |                                                                |                                                              |                                                                  |
|----------------------------------------------------------------------|--------------|------------------------------------------------------------|----------------------------------------------------------------|--------------------------------------------------------------|------------------------------------------------------------------|
| Type number                                                          | Voltage Code | $V_{RRM}$ , Maximum repetitive peak reverse voltage<br>(V) | $V_{RSM}$ , Maximum non-repetitive peak reverse voltage<br>(V) | $V_{DRM}$ , Maximum repetitive peak off-state voltage<br>(V) | $I_{RRM}$ , Maximum reverse leakage current @ $T_{JMAX}$<br>(mA) |
| NTT570                                                               | 60           | 600                                                        | 700                                                            | 600                                                          | max. 220                                                         |
|                                                                      | 80           | 800                                                        | 900                                                            | 800                                                          |                                                                  |
|                                                                      | 100          | 1000                                                       | 1100                                                           | 1000                                                         |                                                                  |
|                                                                      | 120          | 1200                                                       | 1300                                                           | 1200                                                         |                                                                  |
|                                                                      | 140          | 1400                                                       | 1500                                                           | 1400                                                         |                                                                  |
|                                                                      | 160          | 1600                                                       | 1700                                                           | 1600                                                         |                                                                  |
|                                                                      | 180          | 1800                                                       | 1900                                                           | 1800                                                         |                                                                  |

| Electrical Characteristics ( $T_A = 25^\circ\text{C}$ unless otherwise noted) |              |           |                        |
|-------------------------------------------------------------------------------|--------------|-----------|------------------------|
| Parameter                                                                     | Symbol       | Values    | Units                  |
| Maximum average forward current @ $T_J = 85^\circ\text{C}$                    | $I_{T(AV)}$  | 570       | A                      |
| Maximum average RMS forward current                                           | $I_{T(RMS)}$ | 895       | A                      |
| Maximum non-repetitive surge current                                          | $I_{TSM}$    | 19000     | A                      |
| Maximum $I^2t$ for fusing                                                     | $I^2t$       | 1805000   | $\text{A}^2\text{s}$   |
| Forward voltage drop                                                          | $V_{TM}$     | max. 1.45 | V                      |
| Critical rate of rise of on-state current                                     | di/dt        | max. 250  | $\text{A}/\mu\text{s}$ |
| Critical rate of rise of off-state voltage                                    | dv/dt        | max. 1000 | $\text{V}/\mu\text{s}$ |
| Gate current required to trigger                                              | $I_{GT}$     | min. 200  | mA                     |
| Gate voltage required to trigger                                              | $V_{GT}$     | min. 3    | V                      |
| Maximum holding current                                                       | $I_H$        | 150       | mA                     |
| Maximum latching current                                                      | $I_L$        | 300       | mA                     |
| Isolation voltage                                                             | $V_{ISO}$    | 3000      | V                      |

| Thermal & Mechanical Specifications ( $T_A = 25^\circ\text{C}$ unless otherwise noted) |              |               |                           |
|----------------------------------------------------------------------------------------|--------------|---------------|---------------------------|
| Parameter                                                                              | Symbol       | Values        | Units                     |
| Operating junction temperature range                                                   | $T_J$        | -40 to +135   | $^\circ\text{C}$          |
| Storage temperature                                                                    | $T_{stg}$    | -40 to +125   | $^\circ\text{C}$          |
| Thermal resistance, junction to case                                                   | $R_{th(jc)}$ | 0.06          | $^\circ\text{C}/\text{W}$ |
| Mounting torque                                                                        | to heatsink  | $5 \pm 15\%$  | Nm                        |
|                                                                                        | to terminals | $10 \pm 15\%$ |                           |
| Weight                                                                                 | W            | 1500          | g                         |

## Package Outline

(All dimensions in mm)



## Circuit Configuration

| Circuit Description                 | Configuration Code | Circuit Drawing |
|-------------------------------------|--------------------|-----------------|
| Series Connection (doubler circuit) | N                  |                 |

## Ordering Table

| NTT | 570 | N | 160 |
|-----|-----|---|-----|
| 1   | 2   | 3 | 4   |

1 – Power Module

- > DD = Diode-Diode
- > TD = Thyristor-Diode
- > TT = Thyristor-Thyristor

2 – Current Rating =  $I_{T(AV)}$

3 – Circuit Configuration (see Table)

4 – Voltage Code (see Voltage Ratings table)