

## BS6622 - 6.35/11kv single core AWA

Single core armoured cable with XLPE insulation. Rated voltage 6.35/11 KV (Um=12kV)

### Description

Electric cable with copper conductor, semiconductive conductor screen, XLPE insulation, semiconductive insulation screen, copper metallic screen on each core, PVC bedding, aluminium wires armour (AWA), PVC outer sheath

### Application

for energy networks where mechanical stresses are expected. Suitable for underground installation or in ducts

Note: the cable is suitable for rated voltage 6/10 KV (Um=12kV) according to IEC 60502-2



### Standards

**International** IEC 60502-2  
**National** BS 6622

### Characteristics

Construction characteristics	
Conductor material	Copper
Conductor shape	Circular
Conductor flexibility	Stranded class 2
Material of the inner semi-conductor	XLPE-SC
Insulation	XLPE (chemical)
Material of the external semi-conductor	Extruded strippable
Screen	Copper tape
Inner sheath	PVC
Armour type	Aluminium Wire
Outer sheath	PVC
Colour	Red
Lead free	Yes
Halogen free	No



Conductor flexibility  
Stranded class 2



Lead free  
Yes



Halogen free  
No



Rated Voltage U<sub>0</sub>/U  
(U<sub>m</sub>)  
6.35 / 11 kV



Max. conductor temperature in  
service  
90 °C



Flame retardant  
Yes

## BS6622 - 6.35/11kv single core AWA

### Electrical characteristics

Rated Voltage U <sub>0</sub> /U (U <sub>m</sub> )	6.35 / 11 kV
---------------------------------------------------	--------------

### Usage characteristics

Max. conductor temperature in service	90 °C
---------------------------------------	-------

Short-circuit max. conductor temperature	250 °C
------------------------------------------	--------

Flame retardant	Yes
-----------------	-----

### Selling information

On request the cables could be produced with suitable cross-section of metallic screen to meet the requirements of the customers. Please contact us for more information. The permissible current ratings are provided for informative purpose only.



Conductor flexibility  
Stranded class 2



Lead free  
Yes



Halogen free  
No



Rated Voltage U<sub>0</sub>/U  
(U<sub>m</sub>)  
6.35 / 11 kV



Max. conductor temperature in  
service  
90 °C



Flame retardant  
Yes