

NA2XS(F)2Y RE 12/20 kV

Single-core XLPE-insulated cables with PE sheath, longitudinally watertight, solid aluminium conductor

Description

Construction


solid aluminium conductor - conductor screen of semiconducting compound - insulation of cross-linked polyethylen (XLPE) - screen of semiconducting compound - semiconducting swellable tape - screen of copper wires and copper tape - separation tape - PE sheath.

On request we are also delivering the construction with inner rubber sheath.

Application

in ground, outdoors, in water, indoors and in cable ducts

This product is also part of our Windlink® offer dedicated to wind turbines.










Standards

International IEC 60502-2

Characteristics








Construction characteristics	
Conductor shape	Circular solid (RE)
Lead free	Yes
Halogen free	Yes
Insulation	XLPE (chemical)
Material of bedding	SC swelling tape
Screen	Copper wire + copper tape
Outer sheath	PE
Longitudinally watertight	Yes
Usage characteristics	
Packaging	Drum
Minimum installation temperature	-20 °C
Minimum operating temperature	-40 °C
Max. conductor temperature in service	90 °C
Short-circuit max. conductor temperature	250 °C
Bending factor when laying	15 (xD)

						
Lead free Yes	Halogen free Yes	Longitudinally watertight Yes	Minimum installation temperature -20 °C	Minimum operating temperature -40 °C	Max. conductor temperature in service 90 °C	Bending factor when laying 15 (xD)

NA2XS(F)2Y RE 12/20 kV

Selling information

Note: On request we are delivering three single core laid up cables on one drum

						
Lead free Yes	Halogen free Yes	Longitudinally watertight Yes	Minimum installation temperature -20 °C	Minimum operating temperature -40 °C	Max. conductor temperature in service 90 °C	Bending factor when laying 15 (xD)