



Crossbow™

20+ Gbps Orthogonal Architecture Solution



- 20+ Gbps performance
- Meets the IEEE 802.3ap v3.2 10GBASE-KR standard with margin
- XCede® technology optimized for orthogonal midplane architectures
- Demonstrated 100 Ohms ± 5% impedance across an entire link
- De-skewed differential pairs
- Less than 1.5% crosstalk at 50 picoseconds



The Crossbow connector system is the first differential connector truly optimized for orthogonal midplane configurations. The Crossbow™ connector family provides designers with superior electrical performance to 20+ Gbps for orthogonal midplane architectures.

Version	Description/Application	Density	Minimum Slot Pitch
Crossbow (6 x 6)	6-pairs per column by 6-pairs per row on a 4mm pitch	72 differential signal pairs per inch (front and back side of PWB)	1.25" (31,75mm)
Crossbow (4 x 4)	4-pairs per column by 4-pairs per row on a 4mm pitch	32 differential signal pairs per inch (front and back of PWB)	0.95" (24,13mm)
Crossbow 2mm+ (5-Pair)	5-pairs per 2mm column	63 differential signal pairs per inch	1.25" (31,75mm)


Superior Electrical Performance

Crossbow allows designers to take advantage of all the benefits associated with orthogonal midplane architectures as the differential pairs on each side of the midplane share vias creating a straight pass-through connection. This shared via approach combined with the Crossbow footprint, eliminates most electrical problems associated with the typical backplane via stub. This includes eliminating crosstalk in the footprint, reflections, and impedance mismatches — the Crossbow connector system has demonstrated a 100 Ohms ± 5% impedance across a full link.


Crossbow connectors leverage optimized trace geometries, optimized footprint patterns, and an advanced 3-D shielding technique that fully surrounds and isolates the differential signals. The results are minimal transmission loss past 10 GHz, tightly matched impedance, and reduced crosstalk through the connector and the entire system.

Version	Bandwidth	Crosstalk Multi-line Time Domain	Crosstalk Single Aggressor in Frequency Domain	Crosstalk Insertion Loss to Crosstalk Ratio	Impedance
Crossbow (6 x 6)	20+ Gbps	< 1.5% at 50 picoseconds	< -35 dB for any aggressor to 10 GHz	25 dB at 10 GHz	100 ± 5%
Crossbow (4 x 4)	20+ Gbps	< 1.5% at 50 picoseconds	< -35 dB for any aggressor to 10 GHz	25 dB at 10 GHz	100 ± 5%
Crossbow 2mm+ (5-Pair)	12.5 Gbps	< 1.5% at 50 picoseconds	< -40 dB for any aggressor to 5 GHz	25 dB at 5 GHz	100 ± 7%

Crossbow™ differential transmission and multi-line sum-of-voltage crosstalk



Crossbow™ 2mm+ differential transmission and multi-line sum-of-voltage crosstalk



Amphenol TCS


A Division of Amphenol Corporation

Skew Compensated


Crossbow's unique design eliminates the need for designers to compensate for skew and its negative electrical impacts with in-pair skew less than 1.5 picoseconds.

System Solution


In addition to the electrical benefits, the connector provides the overall lowest cost system solution. The Crossbow shared via approach eliminates the need to route high-speed traces across the backplane to connect from the front to back — as required when standard backplane connectors are used in orthogonal midplane applications. This has the advantage of reducing PWB layers by as much as 50% and eliminates the need for backdrilling.



Traditional connector routed differentially in orthogonal midplane (GbX® 5-Pair example)



Amphenol's Crossbow™ optimized pass-through orthogonal midplane solution




Superior Mechanical Robustness

Crossbow meets the most rigorous mechanical requirements. The connector leverages many of Amphenol's proven technologies such as the GbX® 0.018" compliant pin and mating interface to ensure that mechanical integrity will not be an issue.


The Crossbow system includes features on the backplane connector that protect the contacts (blades) from bending during handling, reducing the chances of stubbing during mating with the daughtercard connectors. This is accomplished in the orthogonal configuration with plastic features and end walls that are higher than the signal blades effectively protecting the blades. Crossbow 2mm+ accomplishes the same protection utilizing a strip shield wall in the backplane connector which is higher than the signal blades. In addition to robust guidance, the signal blades are designed to be very rigid utilizing thicker gauges, strengthening ribs, and high performance copper alloys.

Integrated Connector Solutions

Daughtercard connector assemblies utilize a stainless steel organizer which allows signal wafers to integrate with power and guidance. The 6 x 6 Crossbow and 5-pair 2mm+ connectors were designed to fit on the same organizer allowing the designer maximum connector configuration flexibility.



Backplane and daughtercard power modules offer 6 Amps per contact and can be positioned anywhere on the connector organizer. The guide module is available as a wide guide integrated into the backplane module insulator or as a stand-alone board mounted guide pin. The daughtercard guide module includes an ESD contact feature.



Amphenol TCS

A Division of Amphenol Corporation

Amphenol TCS
44 Simon Street
Nashua, NH 03060
603.879.3000

Shanghai, China +86.21.5836.5500
Dublin, Ireland +353.1.241.4000

www.amphenol-tcs.com

Crossbow, GbX, and XCede are trademarks or registered trademarks of Amphenol Corporation. Information contained in this document is summary in nature and subject to change without notice. Appearance of the final, delivered product may vary from the photographs shown herein. Patent: 6,592,381. Other patents pending.

© Amphenol Corporation 2008 • All rights reserved • Printed in USA

ATCS-095-0108-1K