


# Raychem RTD-200

## RTD TEMPERATURE SENSOR FOR AMBIENT SENSING



#### PRODUCT OVERVIEW

The Raychem RTD-200 is a three-wire platinum RTD (resistance temperature detector) typically used with electronic control systems that require accurate ambient temperature sensing. The RTD-200 comes with a 1/2" NPT fitting that installs to the appropriate conduit box. This allows mounting of the RTD in a typical ambient location. This also allows for splicing of RTD extension wire back to the controller.

#### SPECIFICATIONS

Sensor	
Housing	316 stainless steel
Dimensions	3-in (7.6 mm) length, 1/4-in (6 mm) diameter
Accuracy	± 0.3°F (± 0.2°C)
Range	-100°F to 300°F (-73°C to 149°C)
Resistance	100 ohms $\pm$ 0.25 ohm at 0°C $\alpha$ =0.00385 ohms/ohm/°C
Extension wire	
Wire size (each of three)	22 AWG <b>Note:</b> The length of RTD extension wires is determined by the wire gauge used. To reduce the likelihood that electrical noise will affect temperature measurement, keep RTD extension wires as short as possible. Use shielded instrument cable such as Raychem MONI-RTD-WIRE (22 AWG, PVC insulation, -30°F to 140°F, -20°C to 60°C) or Belden 83553 (22 AWG, FEP insulation, -95°F to 395°F, -70°C to 200°C).
Wire dielectric strength	600 V
Length	6 ft (1.8 m)
Outer jacket	Fluoropolymer
Maximum exposure temperature	300°F (149°C)
Sensor fitting	1/2-in (12.7 mm) NPT with sealing washer and nut

#### APPROVALS

Approvals associated with control device. Not to be used in Division 1 areas.



#### NORTH AMERICA

Tel: +1.800.545.6258 Fax: +1.800.527.5703 Tel: +1.650.216.1526 Fax: +1.650.474.7711 thermal.info@pentair.com

#### EUROPE, MIDDLE EAST, AFRICA

Tel: +32.16.213.511 Fax: +32.16.213.603 thermal.info@pentair.com

#### ASIA PACIFIC

Tel: +86.21.2412.1688 Fax: +86.21.5426.2937 cn.thermal.info@pentair.com

### WWW.PENTAIRTHERMAL.COM

LATIN AMERICA Tel: +1.713.868.4800 Fax: +1.713.868.2333 thermal.info@pentair.com

Pentair is owned by Pentair or its global affiliates. All other trademarks are the property of their respective owners. Pentair reserves the right to change specifications without prior notice.

© 2002-2016 Pentair.