

PERFECT PAIR

60W Incandescent Equivalent

4WAC Driver + Module
120VAC ELV Dim, Point Source

- Driver and module engineered for compatibility and warranty
- Driver is industry leading, 120VAC only, dims to less than 20% with recommended ELV dimmers
- Module holes accept off-the-shelf Ledil "CUTE" lens for applications where a directed beam is required
- Wide range of CCT, CRI choices, latest generation LED provides highest efficacy and color consistency



PS3-350C-DIM + BBO3FK

Typical Fixture Applications



pathway



bollard



well



landscape



lantern

See individual data sheets for additional technical information
PS3-350C-DIM and BBO3FK
 Recommended order quantity is module panel size (63) units

| Driver + Module Part Number | CCT (Kelvin) | Minimum CRI | Light Output (Lumens) | Power (WAC) |
|--------------------------------|-----------------|----------------|--------------------------|----------------|
| PS3-350C-DIM + BBO3FK-27-80-01 | 2700 | 80 | 377 | 4.0 |
| PS3-350C-DIM + BBO3FK-30-80-01 | 3000 | 80 | 398 | 4.0 |
| PS3-350C-DIM + BBO3FK-35-80-01 | 3500 | 80 | 416 | 4.0 |
| PS3-350C-DIM + BBO3FK-40-80-01 | 4000 | 80 | 419 | 4.0 |
| PS3-350C-DIM + BBO3FK-50-80-01 | 5000 | 80 | 416 | 4.0 |

WHAT DO I USE FOR A HEATSINK??

Permlight Technologies Retrofit or New Fixture Services Offered

- Recommendations for heatsink and lens materials for optimum performance
- Fixture thermal test "in-situ", TM-21 calculation of lumen depreciation and long life
- Fixture integrating sphere test: lumens, CCT, CRI at fixture level (not IES or LM-79)