

Intrinsically Safe - Gas LIPS® SERIES G112		Part Number Coding				
		G112	Travel	A	Blank	Conn / Cable end
Gauge Head Linear Sensor						
Travel						
mm of stroke	Value					
Electrical Interface						
Input	Output					
+ 5 V dc	See below	A				
Adjusts not available						
Connector / Cable						
3 Core Cable - Radial Gland IP67	Please specify cable length in cm.	Ixx	eg. I2000 specifies 20 metres of 3 core cable with a radial cable gland			
5 Core Cable - Radial Gland IP67	Please specify cable length in cm.	IQxx	eg. IQ2000 specifies 20 metres of 5 core cable with a radial cable gland			
Connector - Axial M12		J				
Connector - Radial		K				
3 Core Cable Axial Gland IP67	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of 3 core cable with an axial cable gland			
5 Core Cable Axial Gland IP67	Please specify cable length in cm.	LQxx	eg. LQ2000 specifies 20 metres of 5 core cable with an axial cable gland			
Tighter Linearity		Zsuffix				
± 0.1% Linearity	from 10mm stroke only	Z650				

Please Note: This sensor must be used with a Galvanic Isolation Amplifier - See G005 sheet for Output options.