

Intrinsically Safe - Dust LIPS® SERIES H117		Part Number Coding								
		H117	Travel	A	Blank	Body & Cable	Option 1	Option 2	Option 3	Z000
Slim-line Linear Sensor										
Travel										
mm of stroke		Value								
Electrical Interface Options										
Input		Output								
+ 5 V dc		See below		A						
Adjusts not available										
Body Style										
Connector - Axial		J								
Connector - Radial		K								
3 Core Cable - Axial Gland		Please specify cable length in cm.		LXX		eg. L2000 specifies 20 metres of 3 core cable with an axial cable gland				
5 Core Cable - Axial Gland		Please specify cable length in cm.		LQXX		eg. LQ2000 specifies 20 metres of 5 core cable with an axial cable gland				
OPTIONS										
Body Fittings										
M5 Rod Eye fitted to body		Only available on lxx Version		N		Option 1				
Push Rod Fittings										
M5 Rod Eye fitted to push rod				U		Option 2				
Non Captive Push Rod										
Push Rod not retained in body				V		Option 3				
Tighter Linearity										
± 0.1% Linearity		from 10mm stroke only		Z650		Zsuffix				

Please Note: This sensor must be used with a Galvanic Isolation Amplifier - See G005 sheet for Output options.