

Part Number Coding

LIPS® SERIES P118		P118	Travel	Electrical Interface	L/J	Option 1	Option 2	Option 3	Option 4	Option 5	Z code
Short Stroke Slim-Line Position Sensor											
Travel											
mm of stroke	Value										
Electrical Interface Options											
Input	Output										
+ 5V dc nom.± 0.5V	0.5 to 4.5V dc ratiometric	A									
24V dc nom. +9-28V	0.5-4.5V dc	G									
24V dc nom. +13-28V	0.5 to 9.5V dc	C									
Adjusts not available											
Cable / Connector											
Cable - Axial Gland IP67	Please specify cable length in cm.	LXX	eg. L2000 specifies 20 metres of cable with an axial cable gland								
Connector - Axial M8 4 pin IP67		J									
OPTIONS											
Housing		Option 1									
Front Flange	N										
Body Clamp		Option 2									
Body Clamps (1 pair)	P										
Spring Return		Option 3									
Spring Return	R										
Plunger End Fitting		Option 4									
Dome End	T										
Plunger (Armature) Guide		Option 5									
Free Plunger (no inner guide bearing)	Not available with option R or T	V									
Tighter Linearity		Zsuffix									
± 0.1% Linearity	from 10mm stroke only	Z650									