

Intrinsically Safe - Gas LIPS® SERIES G117		Part Number Coding								
		G117	Travel	A	Blank	Body & Cable	Option 1	Option 2	Option 3	Option 4
Slim-line Linear Sensor										
Travel										
mm of stroke	Value									
Electrical Interface Options										
Input	Output									
+ 5 V dc	See below	A								
Adjusts not available										
Body Style										
3 Core Cable - Radial Gland	Please specify cable length in cm.	Ixx	eg. I2000 specifies 20 metres of 3 core cable with a radial cable gland							
5 Core Cable - Radial Gland	Please specify cable length in cm.	IQxx	eg. IQ2000 specifies 20 metres of 5 core cable with a radial cable gland							
Connector - Axial		J								
Connector - Radial		K								
3 Core Cable - Axial Gland	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of 3 core cable with an axial cable gland							
5 Core Cable - Axial Gland	Please specify cable length in cm.	LQxx	eg. LQ2000 specifies 20 metres of 5 core cable with an axial cable gland							
OPTIONS										
Body Fittings		Option 1								
M5 Rod End fitted to body	Only available on Ixx Version	N								
Body Clamp		Option 2								
Body Clamps (1 pair)		P								
Push Rod Fittings		Option 3								
M5 Rod End fitted to Push Rod		U								
Non Captive Push Rod		Option 4								
Push Rod not retained in body		V								
Tighter Linearity		Zsuffix								
± 0.1% Linearity	from 10mm stroke only	Z650								

Please Note: This sensor must be used with a Galvanic Isolation Amplifier - See G005 sheet for Output options.