

Intrinsically Safe - Dust LIPS® SERIES H115		Part Number Coding							
		H115	Travel	A	I/L	Option 1	Option 2	Option 3	Option 4
10 bar Submersible Stand Alone Rugged Linear Position Sensor									
Travel									
mm of stroke	Value								
Electrical Interface Options									
Input		Output							
+ 5 V dc		See below		A					
Cable Gland									
3 Core Cable - Radial Gland IP68	Please specify cable length in cm.	Ixx	eg. I2000 specifies 20 metres of 3 core cable with a radial cable gland						
5 Core Cable - Radial Gland IP68	Please specify cable length in cm.	IQxx	eg. IQ2000 specifies 20 metres of 5 core cable with a radial cable gland						
3 Core Cable - Axial Gland IP68	Please specify cable length in cm.	Lxx	eg. L2000 specifies 20 metres of 3 core cable with an axial cable gland						
5 Core Cable - Axial Gland IP68	Please specify cable length in cm.	LQxx	eg. LQ2000 specifies 20 metres of 5 core cable with an axial cable gland						
OPTIONS									
Body Fittings				Option 1					
M8 Rod Eye on Body	Only available with option 1	N							
Body Clamps (1 pair)		P							
Body Clamps (2 pairs)		P2							
Spring Return		Up to 300mm stroke only		Option 2					
Spring return to extended position		R							
Push Rod End Fitting				Option 3					
None - M5 female thread only	Standard option no code	Blank							
Dome End (for use with option R)		T							
M5 Rod Eye on Push Rod		U							
Non Captive Push Rod Tube				Option 4					
Push Rod not retained in body		V							
Tighter Linearity				Zsuffix					
± 0.1% Linearity	from 10mm upto 400mm stroke only	Z650							

Please Note: This sensor must be used with a Galvanic Isolation Amplifier - See G005 sheet for Output options.