



PRO 200 Textured Vinyl Tape

Technical Data Sheet

Pro 200 is a white textured vinyl tape on a liner.

Features & Benefits:

Seaming tape for vinyl faced fiberglass insulation, ie: metal buildings
Resists to water, detergent, alcohol, aliphatic and some aromatic hydrocarbons

Flexible

Conformable

Technical Data

- ⇒ Liner: 42# SCK White coated with silicone on one side
- ⇒ Adhesive: Acrylic
- ⇒ Peel Adhesion: 3.0 lbs per inch
- ⇒ Sheer Strength: 10hrs.
- ⇒ Total Thickness: 3.2 mils
- ⇒ Loop Tack: 1.8lbs per inch
- ⇒ Release Range: 15 to 50g per inch
- ⇒ Adhesive coat weight: 1.75 g/100 in², +/- 10%
- ⇒ Application Conditions: 40°F to 120°F. Apply to clean, dry surfaces for best results.
- ⇒ Storage Conditions: Store at 60°F to 80°F, 50% RH

Application:

Pro 200 is a white textured vinyl tape that is flexible and conformable. Pro 200 offers durability and moisture resistance. This product utilizes a high performance tackified acrylic adhesive. Pro 200 is used as a seaming tape for fiberglass insulation.

Pro 200 is not recommended for use when in contact with active solvents such as ketones, esters and some chlorinated hydrocarbons.

ISO 9001-2008
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234
sales@protapes.com