

PRO 156

5 MIL 3" I.D. Core ADHESIVE
TRANSFER TAPE



Technical Data Sheet

**Pro 156 is a 5 mil adhesive transfer tape
on a kraft liner.**

Features & Benefits:

Extremely high adhesion
Good shear strength
Excellent gap filling properties

Technical Data

- ⇒ Liner: 60# 4 mil Moisture Stable Kraft Liner
- ⇒ Adhesive: 5 mil Acrylic
- ⇒ Thickness without liner: 5.0 mils
- ⇒ Tape Thickness with liner: 9.0 mils
- ⇒ Color: Clear
- ⇒ Adhesion to steel: 100 oz/in
- ⇒ Low temperature application: 10°F
- ⇒ Heat resistance: 250°F
- ⇒ Application Temperature Range: 70°F to 100°F
- ⇒ 3" ID Core
- ⇒ MIL-P-19834B, Amend I
- ⇒ Chemical Resistance: Medium
- ⇒ Not intended for direct UV Light.

Application:

Pro 156 can be used as a laminating adhesive for foam, fabrics, metal or plastic nameplates and is an excellent product for splicing of films, fabrics and foils. It is also suited for joining materials with irregular or textured surfaces.

ISO 9001
Certified



621 Route One South. North Brunswick, NJ 08902

Toll Free #1-800-345-0234

sales@protapes.com