

CABLE TO CONNECTOR CROSS REFERENCE

| Sentinel Connector Recommendation | Quabbin Cable Series | Performance Category | Cable Shielded or Unshielded | Special Notes |
|-----------------------------------|------------------------------------|----------------------|------------------------------|---|
| 110-080810-24 | 9760 | T-1/DS-1/xDSL | Unshielded | 2 pair (.031 inner OD) Must remove outer layer of insulation |
| 110-080820-24 | 9719, 9720, 9722, 9732, 9738, 9770 | T-1/DS-1 | Unshielded | Open Back, Solid or Stranded with Max .040 Diameter Conductor 2 Pair Cables-Must Remove Outer Layer Of Insulation |
| 106-080800-34 | 5500 - 5515 | Category 5e | Unshielded | Standard Back, Solid or Stranded - Most Popular Connector |
| 106-080800-34 | 9469, 9489, 9499 | Category 5e | Unshielded | Standard Back, Solid or Stranded - Most Popular Connector |
| 107-080800-34 | 9469, 9489, 9499 | Category 5e | Unshielded | Standard Back, Solid or Stranded, Snagless Connector |
| 111-08080054L34 | 2200 - 2215 | Category 6 | Unshielded | Solid or Stranded, With Load Bar-Most Popular - DataMax 6 Certified |
| 111-08080062L34 | 2200 - 2215 | Category 6 | Unshielded | Matched Set used with 111-08080063L34, Stranded or Solid, Patch Apps |
| 111-08080063L34 | 2200 - 2215 | Category 6 | Unshielded | Matched Set used with 111-08080062L34, Stranded or Solid, Patch Apps |
| 111S08080054L34 | 2930 - 2941 | Category 6 | Shielded | Solid or Stranded, With Load Bar |
| 112-080800-34 | 2200 - 2215 | Category 6 | Unshielded | Short Body Plug For Over Molding |
| 111-08080095LA4 | 2954 - 2965 | Category 6a | Unshielded | 111-08080062 & 63L34 plugs can also be used |
| 111S08080095LA4 | 2942 - 2953 | Category 6a | Shielded | 111S08080062 & 63L34 plugs can also be used |
| 110-080810-24 | 9760* | T-1/DS-1/xDSL | Shielded | 2 Pair (.031 inner OD)-Must Remove Outer Layer Of Insulation |
| 110S080820-24 | 2900 - 2912 | Category 5e | Shielded | Open Back, Solid or Stranded with Max .040 Diameter Conductor |
| 110S080820-24 | 9720*, 9722*, 9732*, 9738*, 9770* | T-1/DS-1 | Shielded | Open Back, Solid or Stranded with Max .040 Diameter Conductor 2 Pair Cables-Must Remove Outer Layer Of Insulation |
| 111S08080016-34 | 9468 | Category 5e | Shielded | Solid or Stranded with Load Bar - Connector Designed For .042 P/N 9468 Is .044. Will Be Tight Fit but it will work. |
| 111-080800B5LA4 | 2216 - 2230 | Mini-6 28 AWG | Unshielded | |
| 111S080800C7LA4 | 2231 - 2245 | Mini-6a 28 AWG | Shielded | |

*Shielded connectors should ONLY be used if specified by user

It is always best to use the crimp tool made by the manufacturer of the connector. For more information please contact Sentinel Connector Systems Inc, for the proper die part number.