

SiC Schottky Diode

Features:

- ✦ Positive temperature coefficient, great for parallel connection.
- ✦ Switching is not affected by temperature.
- ✦ Max operational temperature: 175°C.
- ✦ 0 Reverse recovery current.
- ✦ 0 Forward recovery voltage.



Benefits:

- ✦ Unipolar device.
- ✦ Greatly reduce switching loss.
- ✦ No thermal breakdown in parallel devices.
- ✦ Reduce system dependence on heat sink.

Applications:

- ✦ Switching Mode Power Supply (SMPS)
- ✦ Power Factor Correction (PFC)
- ✦ Motor drive, PV inverter, Uninterruptible power supply.
- ✦ Wind driven electricity generator, Train hauling system, Electric automobiles.

V_{RRM}	650	V
$I_F, T_c \leq 135^\circ\text{C}$	10	A
Q_c	25	nC



Maximum Ratings:

Parameter	Symbol	Value	Unit	Test Condition
Repetitive Peak Reverse Voltage	V_{RRM}	650	V	$T_j = 25^\circ\text{C}$
Surge Peak Reverse Voltage	V_{RSM}	650	V	$T_j = 25^\circ\text{C}$
DC Blocking Voltage	V_{DC}	650	V	$T_j = 25^\circ\text{C}$
Continuous Forward Current	I_F	29 14 10	A	$T_c = 25^\circ\text{C}$ $T_c = 135^\circ\text{C}$ $T_c = 150^\circ\text{C}$
Repetitive Peak Forward Surge Current	I_{FRM}	50	A	$T_c = 25^\circ\text{C}$, $tp = 10\text{ms}$, Half Sine Wave, $D = 0.3$
Non-repetitive Peak Forward Surge Current	I_{FSM}	70	A	$T_c = 25^\circ\text{C}$, $tp = 10\text{ms}$, Half Sine Wave
Power Dissipation	P_{TOT}	53.2 24	W	$T_c = 25^\circ\text{C}$ $T_c = 110^\circ\text{C}$
Operating Junction Temperature	T_j	-55°C to 175°C	$^\circ\text{C}$	
Storage Temperature	T_{stg}	-55°C to 175°C	$^\circ\text{C}$	


Thermal Characteristics

Parameter	Symbol	Min.	Typ.	Max.	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$		1.29		$^{\circ}\text{C}/\text{W}$


Electrical Characteristics

Parameter	Symbol	Typ.	Max.	Unit	Test Condition
Forward Voltage	V_F	1.5 1.9	1.6 2.1	V	$I_F=10\text{ A}$, $T_j=25^{\circ}\text{C}$ $I_F=10\text{ A}$, $T_j=175^{\circ}\text{C}$
Reverse Current	I_R	10 15	20 30	μA	$V_R=650\text{ V}$, $T_j=25^{\circ}\text{C}$ $V_R=650\text{ V}$, $T_j=175^{\circ}\text{C}$
Total Capacitance Charge	Q_C	25	-	nC	$V_R=650\text{ V}$, $I_F=3\text{ A}$, $di/dt=500\text{ A}/\mu\text{s}$, $T_j=25^{\circ}\text{C}$
Total Capacitance	C	600 59 58	700 62 60	pF	$V_R=0\text{ V}$, $T_j=25^{\circ}\text{C}$, $f=1\text{ MHz}$ $V_R=200\text{ V}$, $T_j=25^{\circ}\text{C}$, $f=1\text{ MHz}$ $V_R=400\text{ V}$, $T_j=25^{\circ}\text{C}$, $f=1\text{ MHz}$


RATING AND CHARACTERISTICS CURVES (SC2S06510A)



RATING AND CHARACTERISTICS CURVES (SC2S06510A)



Package Outline: TO-220



DIM	Millimeters		Inches	
	Min.	Max.	Min.	Max.
A	4.4	4.6	0.173	0.181
C	1.23	1.32	0.048	0.052
D	2.4	2.72	0.094	0.107
E	0.49	0.7	0.019	0.028
F	0.61	0.88	0.024	0.035
F1	1.14	1.7	0.045	0.067
F3		1		0.039
G	4.95	5.15	0.195	0.203
H1	7.7	7.9	0.303	0.311
H2	10	10.4	0.394	0.409
L2	16.4		0.646	
L3	28.9		1.138	
L4	13	14	0.512	0.551
L5	2.65	2.95	0.104	0.116
L6	15.25	15.75	0.600	0.620
L7	6.2	6.6	0.244	0.260
L9	3.5	3.93	0.138	0.155
M	2.6			
V	5°			
V2	30°			
V4	45°			
diam	3.75	3.85	0.148	0.152

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.