



Fast & Effective Polishing System

Vapor Smoothing System to create a polished surface on 3D-Printed Parts

- Excellent solvent containment & NESHAP Compliant
- Reduced Solvent & Operating Costs
- Small Foot-Print
- On Casters for mobility
- Compatible with variety of solvents
- 120% Freeboard
- Easy maintenance

#### Manufactured in the USA by:



Vapor Zone	25" L x 12" W x 16" Tall
Footprint Dimensions (with casters)	44" Lx 49" W x 51" High
Solvent Charge Requirement	9 gallons
NESHAP Compliant Features	Yes—includes, slide lid, 120% freeboard and sub- zero refrigeration coils.
120% freeboard	Yes
Automated Lid (optional)	Yes
PLC Controlled Lift Available	Yes
Primary Refrigeration	Copeland
Primary Refrigeration Coil	Stainless Steel
Sub-Zero Refrigeration	Copeland
Sub-Zero Refrigeration Coil	Stainless Steel Finned
Safety Temperature Limit Controls	Watlow
Controls Present	HTC, LTC, SVC, VU, RT
Low Solvent Level Safety Float	Yes
Filtration Clean-Out Gauge	Yes
Sump Access Door	Yes, 2 doors for easy clean out
Typical Electrical	208V or 240V, 1 PH, 23A

**VS-2 Vapor Polish** 

& Smoothing Unit

3D Printed Part Smoothing System:

### www.SolventEquipment.com

Reliance Specialty Products, Inc. 855 Morse Ave. Elk Grove Village, IL 60007 phone: 847.640.8923 Fax: 847.640.8974 Please Call for a Price Quote (847) 640-8923





**Expanded Vapor Polishing Zone** 



Primary & Sub-Zero Coils running standard refrigerant



**Simple Control Safety Panel** 



855 Morse Ave. Elk Grove Village, IL 60007 Phone: 847.640.8923 Fax: 847.640.8974

# **ULTRA VS-2 Smoothing System Features**

- **NESHAP COMPLIANT** Vapor Degreasing System
- Solid Tank Construction Heavy Gauge 304 Stainless Steel
- Stainless Steel Primary Condensing Coil New Copeland refrigeration system operating with R134A refrigerant
- Sub-Zero Temperature Condensing Coil—Finned stainless steel with Copeland R404A refrigeration system operating to approximately -20F to supplement primary condensation system. Includes defrost cycle, low-temperature condensing coil with condensate trough
- High Volume Condensate Water Separator
- Digital Display Safety Control Panel including HTC, LTC, SVC, VU, RT
- WATLOW Temperature Safety Limit Controls with digital display on Control Panel; temperature set point as well as actual temperature – SVC (Safety Vapor Control), HTC (High Temperature Control), LTC (Liquid Temperature Control) and RT (Refrigeration Temperature Control)
- Solvent Low-Level Float Safety
- Control panel with solvent low level float fault indicator lights (for easy identification of operating fault conditions). "Spray Ready" indicator light and zero coil "Defrost" indicator light, illuminated on/off switches for easy identification of system condition "Heat", "Filtration", Main Power", "Refrigeration" and "Low-Temp Refrigeration"
- Manual Horizontal Slide Lid—for solvent containment
- Casters—for easy movement
- Electric Immersion heat—"Screw-In" Type Elements for easy replacement
- Sump Access Clean-Out Doors Two Sump access doors for ease of maintenance though the clean-out door rather than over the tank top
- One (1) stainless steel workbasket
- Comprehensive 1-Year Manufacturer's Warranty
- ULTRA VS-2 Operator's Manual

www.SolventEquipment.com

(847) 640-8923



Vertical Basket Handling System for loads up to 35 lbs.

# Optional 3D Printed Part Basket Handling System

Automated Vertical Basket Handling System with Electric horizontal slide lid benefits include:

- Precisely timed polishing cycles
- Labor Cost Savings with reduced or eliminated operator processing time
- Processing Consistency with parts processed the same each cycle.
- Reduced Operator Error
- Increased productivity & processing

#### Creates a polished look in seconds!

## 3D DipSmooth Fluid is designed to work with the VS-2 Vapor Smoothing System:

- Very Fast Acting
- Eliminates Imperfections
- Smooths "Layering" Look
- Works on Many Plastics Including: ABS & Polycarbonate
- Non-Flammable
- Replaces Acetone & Toluene



### www.SolventEquipment.com



Please Call For a Price Quote (847) 640-8923

855 Morse Ave. Elk Grove Village, IL 60007 Phone: 847.640.8923 Fax: 847.640.8974