

ICP641414PM

Rechargeable Lithium Ion Polymer Battery Pack 3.7 V
Safety Circuit

Specifications

Renata Type	ICP641414
IEC Designation	ICP071517
Part Number	100694
Contact Method:	Wire AWG 30
Safety Circuit	Yes

Nominal Voltage	3.7 V
Nominal Capacity	95 mAh
Minimum Capacity	85 mAh (0.2C cut off 3.0 V at 20°C)
Internal Impedance	< 550 mΩ / 50% SOC

Thickness (t)	Max 6.8 mm
Length (l)	Max 16.8 mm
Width (w)	Max 14.9 mm
Weight	~ 2.7 g


Charging Characteristic	CC/CV – Constant Current / Constant Voltage
Voltage	4.2 V CV
Current Normal	0.5 C CC – 47.5 mA
Max. Charging Current	1.0 C CC – 95 mA
Temperature at Charging	0 °C 45 °C

Discharge Characteristic	
Cut off Voltage	3.0 V
Max discharge Current	2.0 C – 190 mA (for non continues discharge) 1.0 C – 95 mA (for continues discharge)
Temperature during Discharge	-20 °C ... 60 °C

Cycle Life at Room Temperature	> 80% of minimum capacity after 500 cycles (0.5 C charge, 0.5 C discharge)
--------------------------------	--

Storage Temperature	-20 °C ... 45 °C (0 °C ... 30 °C recommended in case of storage for more than 3 months)
---------------------	---

Dimensions



Information and contents in this data sheet are for reference purpose only. They do not constitute any warranty or representation and are subject to change without notice. For most current information and further details, please contact your Renata representative.

Rev. Li Ion ICP641414 – 11.09