



SolarEdge Single Phase Inverters

For North America

SE3000A-US / SE3800A-US / SE5000A-US / SE6000A-US /
SE7600A-US / SE10000A-US / SE11400A-US



INVERTERS

The best choice for SolarEdge enabled systems

- Integrated arc fault protection (Type 1) for NEC 2011 690.11 compliance
- Superior efficiency (98%)
- Small, lightweight and easy to install on provided bracket
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- Outdoor and indoor installation
- Fixed voltage inverter, DC/AC conversion only
- Pre-assembled AC/DC Safety Switch for faster installation
- Optional built-in revenue grade meter



Single Phase Inverters for North America

SE3000A-US / SE3800A-US / SE5000A-US / SE6000A-US /
SE7600A-US / SE10000A-US / SE11400A-US

	SE3000A-US	SE3800A-US	SE5000A-US	SE6000A-US	SE7600A-US	SE10000A-US	SE11400A-US		
OUTPUT									
Nominal AC Power Output	3300	3840	5000	6000	7680	9980 @ 208V 10000 @ 240V	11520	VA	
Max. AC Power Output	3650	4150	5400 @ 208V 5450 @ 240V	6000	8350	10800 @ 208V 10950 @ 240V	12000	VA	
AC Output Voltage Min.-Nom.-Max.* 183 - 208 - 229 Vac	-	-		-	-		-		
AC Output Voltage Min.-Nom.-Max.* 211 - 240 - 264 Vac									
AC Frequency Min.-Nom.-Max.*	59.3 - 60 - 60.5 (with HI country setting 57 - 60 - 60.5)							Hz	
Max. Continuous Output Current	14	16	24 @ 208V 21 @ 240V	25	32	48 @ 208V 42 @ 240V	48	A	
GFDI	1							A	
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes								
INPUT									
Recommended Max. DC Power** (STC)	4100	4800	6250	7500	9600	12400	14400	W	
Transformer-less, Ungrounded	Yes								
Max. Input Voltage	500							Vdc	
Nom. DC Input Voltage	325 @ 208V / 350 @ 240V							Vdc	
Max. Input Current***	11	13	16.5 @ 208V 15.5 @ 240V	18	23.5	33 @ 208V 30.5 @ 240V	35	Adc	
Max. Input Short Circuit Current	30							Adc	
Reverse-Polarity Protection	Yes								
Ground-Fault Isolation Detection	600k Ω Sensitivity								
Maximum Inverter Efficiency	97.7	98.2	98.3	98.3	98	98	98	%	
CEC Weighted Efficiency	97.5	98	97.5 @ 208V 98 @ 240V	97.5	97.5	97 @ 208V 97.5 @ 240V	97.5	%	
Nighttime Power Consumption	< 2.5							W	
ADDITIONAL FEATURES									
Supported Communication Interfaces	RS485, RS232, Ethernet, ZigBee (optional)								
Built-in Revenue Grade Meter	Optional								
STANDARD COMPLIANCE									
Safety	UL1741, UL1699B, UL1998, CSA 22.2								
Grid Connection Standards	IEEE1547								
Emissions	FCC part15 class B								
INSTALLATION SPECIFICATIONS									
AC output conduit size / AWG range	3/4" minimum / 24-6 AWG				3/4" minimum / 8-3 AWG				
DC input conduit size / # of strings / AWG range	3/4" minimum / 1-2 strings / 24-6 AWG				3/4" minimum / 1-2 strings / 14-6 AWG				
Dimensions with AC/DC Safety Switch (HxWxD)	30.5 x 12.5 x 7 / 775 x 315 x 172		30.5 x 12.5 x 7.5 / 775 x 315 x 191		30.5 x 12.5 x 10.5 / 775 x 315 x 260			in / mm	
Weight with AC/DC Safety Switch	51.2 / 23.2		54.7 / 24.7		88.4 / 40.1			lb / kg	
Cooling	Natural Convection				Fans (user replaceable)				
Noise	< 25				< 50				dBA
Min.-Max. Operating Temperature Range	-13 to +140 / -25 to +60 (CAN version**** -40 to +60)							°F / °C	
Protection Rating	NEMA 3R								

* For other regional settings please contact SolarEdge support.

** Limited to 125% for locations where the yearly average high temperature is above 77°F/25°C and to 135% for locations where it is below 77°F/25°C.

For detailed information, refer to http://www.solaredge.us/files/pdfs/inverter_dc_oversizing_guide.pdf.

*** A higher current source may be used; the inverter will limit its input current to the values stated.

**** CAN P/Ns are eligible for the Ontario FIT and microFIT (microFIT exc. SE11400A-US-CAN).



RoHS

© SolarEdge Technologies, Inc. All rights reserved. SOLAREEDGE, the SolarEdge logo, OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 03/2014. V.01. Subject to change without notice.

Distributed by:



Solar Energy
Systems

Erving, MA

413-829-1103

www.RenewedbytheSon.com