



PIN	SYMBOL	RX020A-01
1	DB15	
2	DB14	
3	DB13	
4	DB12	
5	DB11	
6	DB10	
7	DB9	
8	DB8	
9	GND	
10	DB7	
11	DB6	
12	DB5	
13	DB4	
14	DB3	
15	DB2	
16	DB1	
17	DB0	
18	IDVCC	
19	VDD	
20	RD	
21	WR	
22	RS	
23	CS	
24	RESET	
25	NC	
26	GND	
27	A	
28	K1	
29	K2	
30	K3	
31	Y+(YD)	
32	Y-(YD)	
33	X+(XR)	
34	X-(XL)	
35	NC	
36	NC	

- NOTE:
1. LCD TYPE: 2. 0" TFT
 2. LCD IC: IL19225G
 3. VIEWING DIRECTION: 12:00' CLOCK
 4. BACKLIGHT: 7 CHIPS WHITE LED
 5. OPERATON TEMP: -20°C ~70°C
 6. STORAGE TEMP: -30°C ~80°C
 7. GENERA TOLERANCE: ±0.2
 8. Connector: FPC

REV	Revision content description	Date
A	FIRST ISSUE	2013.12.10

 深圳市如新电子有限公司			
TOLERANCE (公差)	Mod.Name	PART.Name	
TOLERANCE UNLESS OTHERWISE SPECIFIED	X.XX±0.3	RX020A-01	LCM
UNIT	DESIGNED(structure)	DESIGNED(electron)	APPROVED
mm	JHJ		
			DRAWING NAME
			ASSEMBLE