

# ROITHNER LASERTECHNIK PRESENTS

---

## NEW MID-IR LASER DIODES



2.0 um and 2.3 um MID-IR laser diodes, 5.6 mm with monitor photodiode, **room temperature operation !**

RLTCM-2010D, **2.0 um**, 10 mW cw, 5.6 mm with monitor photodiode, datasheet on request

RLTCM-2025D, **2.0 um**, 25 mW cw, 5.6 mm with monitor photodiode, [datasheet](#)

RLTCM-2307D, **2.3 um**, 7.5 mW cw, 5.6 mm with monitor photodiode, datasheet on request

RLTCM-2310D, **2.3 um**, 10 mW cw, 5.6 mm with monitor photodiode, [datasheet](#)

RLTCM-2325D, **2.3 um**, 25 mW cw, 5.6 mm with monitor photodiode, datasheet on request

custom wavelengths from 1.8 um - 2.6 um available on request

unique features:

- working at room temperature (Top: 0 - 70°C)
- very low threshold current
- low operating current
- low operating voltage
- standard TO56 package
- integrated monitor photodiode

find these laser diodes in our pricelist on page 6

find more MID-IR laser diodes up to 13.9 um [here](#)

find more MID-IR LEDs up to 7.0 um [here](#)

---

Download our [pricelist](#), 1.2 M, pdf, updated Feb. 18, 2009

---

Do you have the need for special optoelectronics or laser components? **What are you looking for?**

Please let us know! We will try to make you an offer.

[sourcing@roithner-laser.com](mailto:sourcing@roithner-laser.com)

---

[thank you for visiting our web site](#)

---

Best regards,

Andreas Roithner

ROITHNER LASERTECHNIK GmbH

Wiedner Hauptstrasse 76

1040 Vienna, Austria, Europe

Tel.: +43-1-586 52 43 - 0

Fax.: +43-1-586 52 43 44

[office@roithner-laser.com](mailto:office@roithner-laser.com)

[www.roithner-laser.com](http://www.roithner-laser.com)

Disclaimer:

Since you have received this message you have either responded to one of our offers in the past or your address has been registered with us. If you wish to be removed please reply to: [remove@roithner-laser.com](mailto:remove@roithner-laser.com)