
ROITHNER LASERTECHNIK PRESENTS...

NEW 405 nm LASER DIODES



405 nm laser diode, cw, [price list page 1](#)

RLT405-10MG, **405 +/- 10 nm**, max. 20 mW, 75 °C, 5.6 mm, with photodiode
DL-4146-301D, **410 +/- 5 nm**, max. 20 mW, 60 °C, 5.6 mm, no photodiode

NEW 405 nm LASERPOINTERS



405 nm laserpointer, [price list page 77](#)

GLP-405-5, **405 nm**, 5 mW, 2 x CR2 lithium batteries, 80 g, size 17 x 150 mm
GLP-405-10, **405 nm**, 10 mW, 2 x CR2 lithium batteries, 80 g, size 17 x 150 mm
GLP-405-20, **405 nm**, 20 mW, 2 x CR2 lithium batteries, 80 g, size 17 x 150 mm

NEW 405 nm LASER DIODE MODULE



405 nm laser diode module, [price list page 16](#)

RLDE405-12-6, **405 nm**, 12 mW, 0.6 mrad, focusable, 22 x 65 mm, 6 VDC, <60 mA

NEW 405 nm LASER DIODE MODULES



405 nm laser diode modules, [price list page 16](#)

RLTMDL-III-405-10-5, **405 nm**, 10 mW cw, laser stability <5%, power supply 90-264 VAC
RLTMDL-III-405-20-5, **405 nm**, 20 mW cw, laser stability <5%, power supply 90-264 VAC
RLTMDL-III-405-50-5, **405 nm**, 50 mW cw, laser stability <5%, power supply 90-264 VAC
RLTMDL-III-405-60-5, **405 nm**, 60 mW cw, laser stability <5%, power supply 90-264 VAC
RLTMDL-III-405-10-3, **405 nm**, 10 mW cw, laser stability <3%, power supply 90-264 VAC
RLTMDL-III-405-20-3, **405 nm**, 20 mW cw, laser stability <3%, power supply 90-264 VAC
RLTMDL-III-405-50-3, **405 nm**, 50 mW cw, laser stability <3%, power supply 90-264 VAC
RLTMDL-III-405-60-3, **405 nm**, 60 mW cw, laser stability <3%, power supply 90-264 VAC

NEW 445 nm LASER DIODE MODULES



445 nm laser diode modules, [price list page 16, 17](#)

RLTMDL-III-445-10-3, **445 nm**, 10 mW cw, laser stability <3%, power supply 90-264 VAC
RLTMDL-III-445-10-5, **445 nm**, 10 mW cw, laser stability <5%, power supply 90-264 VAC

NEW HIGH POWER RED LASER DIODES



635 nm and 650 nm high power laser diodes, [price list page 1](#)

QL63K4SA-L, **635 nm**, 60 mW, sm, 40 °C, 5.6 mm
RLT635-100G, **635 nm**, 100 mW, mm, 9 mm
RLT635-150-C, **635 nm**, 150 mW, mm, C-mount
RLT635-150-TO3, **635 nm**, 150 mW, mm, TO3
RLT635-300-TO3, **635 nm**, 300 mW, mm, TO3
RLT635-500-TO3, **635 nm**, 500 mW, mm, TO3
QL65L6SA, **650 nm**, 80 mW, sm, 60 °C, 5.6 mm
RLT65300T, **650 nm**, 300 mW, mm, TO3, w/o photodiode
RLT650-1000-C, **650 nm**, 1W, mm, c-mount

NEW PULSED INFRARED LASER DIODES



904 nm pulsed high power laser diodes, [price list page 8](#)

PLD904-2-MG, **904 nm**, 2 W-pulse, 40 x 1 μm^2 , 5.6 mm
PLD904-4-MG, **904 nm**, 4 W-pulse, 60 x 1 μm^2 , 5.6 mm
PLD904-5-MG, **904 nm**, 5 W-pulse, 75 x 1 μm^2 , 5.6 mm
PLD904-10-MG, **904 nm**, 10 W-pulse, 150 x 1 μm^2 , 5.6 mm
PLD904-2-T, **904 nm**, 2 W-pulse, 40 x 1 μm^2 , TO-46
PLD904-4-T, **904 nm**, 4 W-pulse, 60 x 1 μm^2 , TO-46
PLD904-5-T, **904 nm**, 5 W-pulse, 75 x 1 μm^2 , TO-46
PLD904-10-T, **904 nm**, 10 W-pulse, 150 x 1 μm^2 , TO-46



pricelist, 1.2M, updated September 3, 2008

[download_pricelist](#)



[visit our web site](#)

Best regards,

Andreas Roithner

ROITHNER LASERTECHNIK GmbH
Wiedner Hauptstrasse 76
1040 Vienna, Austria, Europe
Tel.: +43-1-586 52 43 - 0
Fax.: +43-1-586 52 43 44
e-mail: office@roithner-laser.com
web: <http://www.roithner-laser.com>

Disclaimer:

Since you have received this message you have either responded to one of our offers in the past or your address has been registered with us. If you wish to be removed please reply to: remove@roithner-laser.com