



# Extreme Flash 9001

## CYANOACRYLATE ACCELERATOR

### Product Description

**Extreme Flash 9001** enhances the curing of EXTREME Cyanoacrylates where low humidity levels or surface acidity may exist. This product is also used for fillet conditions or when gap filling between substrates.

**Extreme Flash 9001** can be pre-applied to the opposite surface from the adhesive or post applied to the adhesive joint by brush, pump sprayer, or dropper.

### Shelf Life

12 months @ 40°F when stored and sealed in original containers.

### Curing Performance

The gap of the bond line will affect set speed. Smaller gaps tend to increase the speed. Activators can be applied to improve set speed but may also impair overall adhesive performance.

### Storage

Products should be stored unopened in a cool, dry place out of direct sunlight

Contact an **EXTREME ADHESIVES®** Adhesive Applications Specialist for further recommendations on adhesive selection.

### Physical Properties

#### Typical Uncured Properties (liquid)

Solvent Based	Heptane
Appearance	Colorless Liquid
Flashpoint (TCC)	20-30°F
Specific Gravity	0.715
Viscosity (cPs @ 68F)	1 cP
Percent Volatiles (by Weight)	100% @ 70F
Boiling Point	N/D
Odor	Pungent
Vapor Density(Air=1)	Heavier than Air

### Instructions for Use

Surfaces to be bonded should be clean and dry. Dispense a drop or drops of an cyanoacrylate to one surface only.

Brush, spray, or wipe FLASH accelerators on surface as needed.

Can be pre-applied or post-applied to bond area. Let FLASH evaporate if pre-applying.

**NOTE:** May adversely affect some plastics and other materials. **Test First.**

The properties represented herein are TYPICAL VALUES and not intended for use in specifications. **Extreme Adhesives, Inc.** MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE. While the information presented is believed to be accurate, no warranty or recommendation is made as to application. Determination of product suitability is the sole responsibility of the user. Suggestions made do not constitute any guarantee in as much as use conditions are beyond our control.

EXTREME ADHESIVES, INC. • 63 EPPING ROAD • PO BOX 1445 • RAYMOND, NH 03077  
TEL: 603-895-4028 • TOLL FREE: 800-888-GLUE • FAX: 603-895-6236 • WWW.EXTREMEADHESIVES.COM

© 09/16/2010