



Material Safety Data Sheet

1- Chemical Product and Company Identification:

Product Name: **Extreme Flash 9001**
Product Type: Cyanoacrylate Accelerator
Emergency Number: 800-535-5053

2- Composition/Information on Ingredients:

<u>Hazardous Component</u>	<u>CAS Number</u>	<u>%</u>
Heptane	142-82-5	70-80
Acetone	67-64-1	20-30
N,N-Dimethyl-P-Toluidine	99-97-8	1.0-3.0

<u>Exposure Limits (TWA)</u>	<u>ACGIH (TLV)</u>	<u>OSHA (PEL)</u>	<u>OTHER</u>
Heptane	400 ppm	500 ppm	no data
Acetone	750 ppm	750 ppm	none
N,N-Dimethyl-P-Toluidine	no data	no data	no data

3- Hazards Identification:

Toxicity: Possible eye and respiratory irritant. Narcotic at high concentrations. Prolonged inhalation may cause headaches. Moderately toxic by ingestion. Liquid may dry out skin.

Primary routes of Entry: Inhalation, Ingestion, contact.

Signs of exposure: Vapors irritate eyes, nose, and throat. Liquid is an eye irritant and may irritate skin.

4- First Aid Measures:

Ingestion: Give water to dilute. Do not induce vomiting. Keep individual calm and seek medical attention.

Inhalation: Remove to fresh air. If symptoms persist, obtain medical attention.

Skin contact: Wash in warm water.

Eye contact: Flush with warm water. Seek medical attention.

5- Fire Fighting Measures:

Flash Point: 20-30°F, Tag Closed Cup
Extinguishing Media: Foam, Dry Chemical or Carbon Dioxide
Unusual Fire or Explosion Hazards: None.
Special Fire Fighting Procedures: N/A.
Hazardous Products Formed by Fire or Thermal decomposition: Irritating Organic Vapors

6-Accidental Release Measures

Steps to be taken in case of spill or leak: Avoid flame and sparks. Maintain adequate ventilation. Soak up in an inert absorbent and store in a closed container until disposal.

7- Handling and Storage:

Safe storage: Store away from flame and sparks.
Handling: Keep container tightly closed. Avoid contact with skin. Avoid breathing vapors. Do not use around heat, sparks, or open flame.

8- Protective Equipment:

Ventilation: Local exhaust ventilation recommended to maintain vapor level below TLV.
Respiratory protection: Not applicable with good local exhaust.
Skin: Polyethylene or non-reactive gloves.
Eye protection: Safety glasses or goggles with side shields.

9- Physical and Chemical Properties:

Appearance: Clear liquid
Odor: Sharp, pungent
Boiling Point: 133°F
Vapor Pressure: 181.7mmHg @68°F
Vapor Density: n/a
Evaporation rate: Slower than ethyl ether
Specific Gravity: .877 @ 77°F
Solubility in water: Miscible
Volatile Organic Compound: (EPA Method 24) < 80.0%

10- Stability and Reactivity

Stability: Stable
Hazardous Polymerization: Will not occur
Incompatibility: Avoid contact with strong oxidizing agents.

11- Toxicological Information

See Section 3

12-Ecological Information

No Data

13- Disposal Considerations:

Disposal procedures: Incinerate or dispose of in an approved landfill in accordance with local and EPA regulations.

14- Transportation Information:

Domestic Ground Transport:

Proper shipping name: Consumer Commodity (not more than one liter)
Heptane Solutions (not more than one liter)

Hazard class or division: ORM-D (Not more than one liter)
Class 3, Packing Group II (More than one liter)

Identification number: None (Not more than one liter)
UN 1206 (More than one liter)

International Air Transportation:

Proper shipping name: Consumer Commodity (not more than one liter)
Heptane Solutions (not more than one liter)

Hazard class or division: ORM-D (Not more than one liter)
Class 3, Packing Group II (More than one liter)

Identification number: None (Not more than one liter)
UN 1206 (More than one liter)

Water Transportation (IMO/IMDG)

Proper shipping name: Consumer Commodity (not more than one liter)
Heptane Solutions (not more than one liter)

Hazard class or division: ORM-D (Not more than one liter)
Class 3, Packing Group II (More than one liter)

Identification number: None (Not more than one liter)
UN 1206 (More than one liter)

15- Regulatory Information

US Federal Regulations

TSCA (Toxic Substances Control Act) Status

TSCA (United States) The intentional ingredients of this product are listed.

CERCLA RQ (Reportable Quantity) – 40 CFR 302.4 (a)

<u>Component</u>	<u>RQ (lbs.)</u>
Acetone	5000
SARA 302 Components – 40 CFR 355 Appendix A:	NONE
Section 311/312 Hazard Class – 40 CFR 370.2	
Immediate(x) Delayed(x) Fire(x) Reactive() Sudden Release of Pressure()	
SARA 313 Components – 40 CFR 372.65:	NONE
International Regulations	
Inventory Status:	Not Determined

State and Local Regulations

CA Proposition 65:

The following statement is made in order to comply with the California Safe Drinking Water and Toxic Enforcement Act of 1986: This product contains the following substance known to the state of California to cause reproductive harm; None

16: Other Information:

Hazard	NFPA Hazard Code®	HMIS Hazard Code®
Health	1	1
Fire	3	3
Reactivity	0	0
Specific Hazard	N/A	Personal Protection See Section 8

NFPA is a registered trademark of the National Fire Protection Association.

HMIS is a registered trademark of the National Paint and Coatings Association.

The properties represented herein are TYPICAL VALUES and not intended for use in specifications. **Extreme Adhesives, Inc.** MAKES NO EXPRESS OR IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS OR OTHERWISE. While the information presented is believed to be accurate, no warranty or recommendation is made as to application. Determination of product suitability is the sole responsibility of the user. Suggestions made do not constitute any guarantee in as much as use conditions are beyond our control.

Issue date: 09/16/2010