

Parabond M-355

High Performance General Purpose Adhesive

M-355 High Performance General Purpose Adhesive is designed to perform on a multitude of substrates such as high pressure laminates, wood, polyurethane foams, fabrics, paper and many others.

THE M-355 IS NOT RECOMMENDED FOR POST-FORMING LAMINATES OR FOR USE ON VINYL ACCESSORY PRODUCTS SUCH AS REDUCER STRIPS, VINYL STAIR NOSINGS, ETC.

Its unique lace spray pattern offers low soak-in for better adhesion and extended coverage. It has a fan tip for controlled placement of the glue. This product offers a fast tack while being economical for the user.

SURFACE PREPARATION:

Materials to be bonded must be clean and dry, free of oil, dirt, paint, moisture, grease, etc. Adhesives and substrates must be 65°F or higher prior to, during and after bonding.

DIRECTIONS:

SHAKE WELL BEFORE USING

FOR INDUSTRIAL USE ONLY

- 1. Hold M-355 six to eight inches from surface to be bonded and apply a uniform coating.
- 2. For porous materials allow several seconds but no more than five minutes before bonding.

- 3. Then bond together while still tacky.
- 4. On non-porous materials spray both surfaces and allow one minute before bonding.
- 5. For a non-permanent bond, apply lightly to one surface, wait five minutes before bonding.
- For non-metallic substrates, compatibility testing is recommended of production parts in typical operating environments.
- It is the sole responsibility of the installer to determine the suitability and compatibility of the adhesive for the end user's intended use.

CLEAN-UP: PARABOND M-315.

SHELF LIFE:

Limited to one year from date of manufacture

FOR MORE INFORMATION, READ MATERIAL SAFETY DATA SHEET

KEEP OUT OF REACH OF CHILDREN.

WARRANTY:

Royal Adhesives and Sealants offers a limited warranty for this product when used in accordance with printed specifications. A copy of the limited warranty can be obtained by calling technical service at 800 763-7272 or visiting www.parabond.com.