

Technical Data Sheet

CAR90UUSB Car/Truck Power Adapter



90 Watt automobile power adapter

Features:

- Wide input voltage range
- Available USB charging port
- 90 Watt continuous output power (85W main-output + 5W USB-output)
- Ultra compact and lightweight car adapter
- All output voltages and currents can be configured via the multiple connector system (MCS)
- Worldwide approvals
- High safety standards (e. g. protection against short circuit, over current, over voltage, over temperature)
- For use in cars and trucks

Applications:

- Suitable for portable or mobile devices
- Simultaneous power for a mobile computing and works with e. g. a laptop and USB compatible device

Specification

Input	
Voltage range	11 - 32VDC
Switch off voltage	10VDC
Standby current	Typical 40mA @ 11V input Typical 80mA @ 32V input
Input fuse	12A (in CLP)
Protection	Reverse polarity (input fuse in CLP) Under voltage protection Over temperature protection (latch-off reset)

Output	
Output 1 (main)	
Voltage range	10 - 24VDC nominal
Power	85W continous
Initial set tolerance	±3% max.
Load regulation ⁽¹⁾	- 80mV max. / A
Line regulation	±1% max.
Ripple & noise ⁽²⁾	< 200mV _{pk-pk}
Current limit	Constant current, 6A max.
Protection	Short circuit Over current protection (current limitation) Over voltage protection (latch-off reset) Over temperature protection (latch-off reset)
Output 2 (USB)	
Voltage	5VDC nominal
Current / Power	1A max. / 5W max.
Total tolerance ⁽³⁾	±5% max.
Protection	Short circuit Over current protection

Notes

1. Load regulation is measured at the output connector and includes the voltage drop across the output cable.
2. Measured with a 0.1µF ceramic and a 10µF electrolytic capacitors across the output terminals. The oscilloscope bandwidth is set at 20MHz a co-axial cable will be used to measure it. The test condition is maximum load.
3. Power losses of input and output cables are not considered here.

Technical Data Sheet

CAR90UUSB Car/Truck Power Adapter



Environmental	
Cooling	Convection cooled
Temperature	Operating: -20°C to 40°C Non-operating: -40°C to 85°C
Pressure & altitude	Operating: 1200hPa to 795hPa, max. 2000m above sea level Non-operating: 1200hPa to 115hPa, max. 15000m above sea level
Humidity	5 to 95% r.H., non-condensing

General	
Input connector	Cigarette lighter adapter (CLP)
Output connector (output 1)	Customer-specific with multiple connector system
Output connector (output 2)	USB receptacle, Type A
Efficiency ⁽³⁾	typical 96% at 100% load
MTBF	>20000h @ 25°C ambient temperature and G _B per MIL-HDBK217F
Green procurement	WEEE RoHS
Indicator green LED	On: Flashing: Off: Power Failure Power on off
Ingress protection rating	IEC60529, IP40

Safety & EMC		
Regulatory approvals	Europe International USA/Canada Australia	CE CB Report IEC60950-1 cULus UL60950-1 RCM
Electromagnetic emissions	Europe USA	EN55022 class B, EN55024 FCC15 class B
Electromagnetic immunity	ESD immunity Electromagnetic field immunity Electrical fast transient/burst immunity test ISO-Impulses UNECE vehicle regulation	IEC61000-4-2, 4kV contact / 8kV air IEC61000-4-3, 80-2700MHz, 3V/m, AM 80%/1kHz IEC61000-4-4, +/-1kV, 5/50ns ISO7637-2, pulses 1, 2a, 2b, 3a, 3b, 4 E13 ECE Reg. 10

- other approvals on request

Mechanical Details	
Housing dimensions (LxWxH)	115 x 53.7 x 21.5mm, without cables and connectors
Input cable length	100cm ±5%
Output cable length	100cm ±5%
Weight	250g, without cables and connectors

Germany/Headquarters	USA	Hong Kong	China
RRC power solutions GmbH Technologiepark 1 D-66424 Homburg / Saar	RRC power solutions Inc. 18340 Yorba Linda Blvd., Suite 107-437 Yorba Linda, CA 92886-4104	RRC power solutions Ltd. S-V,6/F, Valiant Industrial Centre 2-12 Au Pui Wan Street Fo Tan, N.T., Hong Kong	RRC power solutions Ltd. Room 520, Yuanlin Building, Aiguo Road No. 3066, Luohu District, Shenzhen 518021
Tel.: +49 6841 98090 Fax: +49 6841 9809280 Email: sales@rrc-ps.de Web: www.rrc-ps.de	Tel.: +1 714 777 3604 Fax: +1 714 777 3658 Email: usa@rrc-ps.com Web: www.rrc-ps.com	Tel.: +852 2376 0106 Fax: +852 2375 0107 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com	Tel.: +86 755 8374 1908 Fax: +86 755 8374 1861 Email: hkrrc@rrc-ps.cn Web: www.rrc-ps.com