

TECHNICAL DATA
DATA SHEET 193, REV. C.3

AVAILABLE AS

1N5819-1, 1N5819UR-1
JAN EQUIVALENT:
SJ5819-1/SJ5819UR-1*
SV5819-1/SV5819UR-1*
SX5819-1/SX5819UR-1*
SS5819-1/SS5819UR-1*

HERMETIC AXIAL LEAD / MELF SCHOTTKY BARRIER DIODE

DESCRIPTION: A 45 VOLT, 1.0 AMP, AXIAL LEAD/SURFACE MOUNT SCHOTTKY BARRIER DIODE.

MAXIMUM RATINGS

All ratings are at $T_A = 25^\circ\text{C}$ unless otherwise specified.

RATING	CONDITIONS	MIN	TYP	MAX	UNIT
Peak Inverse Voltage (PIV)		-	-	45	Vdc
Average DC Output Current (I_o)	See Notes	-	-	1.0	Amps
Peak Single Cycle Surge Current (I_{fsm})	$t_p = 8.3$ ms Single Half Cycle Sine Wave, Superimposed On Rated Load	-	-	25	Amps(pk)
Thermal Resistance (θ_{JL})	Junction to Lead $d = 0.375$ "	-	-	70	$^\circ\text{C/W}$
Thermal Resistance (θ_{JEC})	Junction to Endcap	-	-	40	$^\circ\text{C/W}$
Junction Temperature (T_J)	-	-55	-	+125	$^\circ\text{C}$
Operating Temperature (T_{op})	-	-55	-	+125	$^\circ\text{C}$
Storage Temp. (T_{stg})	-	-55	-	+150	$^\circ\text{C}$

ELECTRICAL CHARACTERISTICS


CHARACTERISTIC	CONDITIONS	MIN	TYP	MAX	UNIT
Maximum Forward Voltage (V_f)	$I_F = 1.0\text{A}$ (300 μsec pulse, duty cycle < 2%)	-	-	0.49	Volts
Maximum Instantaneous Reverse Current At Rated (PIV)	$T_A = 25^\circ\text{C}$ $T_A = 100^\circ\text{C}$	-	-	50 5.0	μAmps mAmps
Junction Capacitance (C_J)	$V_R = 5$ Vdc $0.01 \leq f \leq 1\text{MHz}$ $V_{sig} = 15$ mV p-p	-	-	70	pF

- Notes:**
- All ratings are at $T_A = 25^\circ\text{C}$ unless otherwise specified.
 - Maximum storage temperature range: -55°C to $+150^\circ\text{C}$.
 - Maximum operating temperature range: -55°C to $+125^\circ\text{C}$ (1N5819-1, 1N5819UR-1).
 - Derate linearly at 14 mA/ $^\circ\text{C}$ above T_L or $T_{EC} = +55^\circ\text{C}$ (1N5819-1), where T_{EC} is at $L = .375$ inch.


**Sensitron space equivalent diodes are manufactured and screened to MIL-PRF-19500 flow and guidelines starting from wafer fabrication through assembly and testing using our internal specification.*

PACKAGE DIMENSIONS:

AXIAL



MELF




SCHOTTKY BARRIER		1N5819-1			
PACKAGE STYLE	DIMENSIONS - INCHES (MILLIMETERS)				
	ϕB	ϕD	G	L	
DO-41	.028/.034 0.71/0.86	.08/.107 .203/.272	.160/.205 .406/.521	1.00/1.30 2.54/3.302	


SCHOTTKY BARRIER		1N5819UR-1			
PACKAGE STYLE	DIMENSIONS - INCHES (MILLIMETERS)				
	A	B	C	D	
DO-213AB	.189/.205 .480/.521	.016/.022 0.41/0.56	0.001 Min 0.03 Min	.094/.105 2.39/2.67	

GRAPHS:


Typical Forward Characteristics



Typical Reverse Characteristics



Typical Junction Capacitance



PART ORDERING INFORMATION

The following part numbers can be purchased in either axial or surface mount devices and screened and tested to the military screening flow. The parts are marked in accordance with the testing performed, example:

Sensitron Screening Level	Part Number- Leaded Package (example for 1N5819-1)	Part Number- Surface Mount Package (example for 1N5819UR-1)
1N	1N5819-1	1N5819UR-1
SJ	SJ5819-1	SJ5819UR-1
SX	SX5819-1	SX5819UR-1
SV	SV5819-1	SV5819UR-1
SS	SS5819-1	SS5819UR-1

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.