



RAPIDSTOCK

RWM Caster's Soft Rubber Wheels are manufactured of quality materials with a resilient rubber tread bonded to a hard rubber core. These wheels are an economical choice for moving equipment.



SRO-3512-06

Features

Wheel Bearing: Choice of straight roller bearing or oilite bearings **Temperature Range:** -40°F to 120°F

Applications

RWM Caster's <u>Soft Rubber Wheels</u> are a good choice for those applications where the average load is light with occasional loads using the full capacity of the wheel. Soft Rubber Wheels offer floor protection but can leave black marks on floors. Soft Rubber Wheels wear on rough surfaces and can become brittle if left outdoors, exposed to the elements. Economical in smaller sizes, Soft Rubber Wheels become more expensive in larger sizes, especially when premium rubber material is used.

options

DC Dust Cover **TG** Thread Guards **WS** Wheel Seals

Specifications

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Straight Roller Bearing	Plain, Oilite, Celcon Bearing	Hub Length	Approx Weight
3"	1-1/4"	150	5/16"		SRO-0312-05	1-1/2"	0.7
3"	1-1/4"	150	3/8"		SRO-0312-06	1-1/2"	0.7
3-1/2"	1-1/4"	150	5/16"		SRO-3512-05	1-1/2"	0.8
3-1/2"	1-1/4"	150	3/8"		SRO-3512-06	1-1/2"	0.8
4"	1-1/4"	180	5/16"		SRO-0412-05	1-1/2"	1.1
4"	1-1/4"	180	3/8"		SRO-0412-06	1-1/2"	1.1
4"	1-1/2"	200	1/2"	SRR-0415-08	SRO-0415-08	1-7/8"	1.3
4"	1-1/2"	200	5/8"	SRR-0415-10	SRO-0415-10	1-7/8"	1.3
4"	1-1/2"	200	3/4"	SRR-0415-12		1-7/8"	1.3