



1225 Isley Road, Gastonia, NC 28052
 Phone: 800-634-7704 Fax: 800-253-6634
 www.rwmcasters.com

Pneumatic Wheels

FN Wheels



RWM Caster's **Pneumatic Wheels** provide smooth, shock-resistant operation for delicate instruments and breakable components. Our *Pneumatic Wheels* are suggested for indoor and outdoor use where product protection is required. *RWM Casters Pneumatic Wheels* offer the maximum in floor protection and move freely over obstructions and rough floors.



FNR-1648-20

Features

Wheel Bearing: Choice of straight roller, ball or tapered roller bearings.
Operating Temperature Range: -26 to 220F

Applications

- Aerospace
- Tow-lines
- Automotive
- Boat Manufacturing
- Product Protection

options

FF Foam Filled
WS Wheel Seals
ZF Zerk Fitting

Specifications

Wheel Diameter	Wheel Width	Ply Rating	lbs. Capacity	Axle Diameter	Straight Roller Bearing	Ball Bearing	Tapered Roller Bearing	Hub Length	Approx Weight
9.0"	2.80/4	4	300	1/2"	FNR-0828-08	FNB-0828-08		3-1/2"	4.5
9.0"	2.80/4	4	300	3/4"	FNR-0828-12	FNB-0828-12		3-1/2"	4.5
10.9"	4.10/4	4	480	1/2"	FNR-1041-08	FNB-1040-08		3-1/2"	5.5
10.9"	4.10/4	4	480	3/4"	FNR-1041-12		FNT-1041-12	3-1/2"	5.5
10.9"	4.10/4	4	480	1"	FNR-1041-16			3-1/2"	5.5
13.0"	4.10/6	4	500	3/4"	FNR-1241-12	FNB-1241-12	FNT-1241-12	4-1/2"	6.5
13.0"	4.10/6	4	500	1"	FNR-1241-16			4-1/2"	6.5
15.1"	5.30/6	4	870	3/4"	FNR-1448-12	FNB-1448-12		4-1/2"	9
15.1"	5.30/6	4	870	1"	FNR-1448-16			4-1/2"	9
16.3"	4.80/8	4	1000	1"	FNR-1648-16		FNT-1648-16	4-1/2"	12
16.3"	4.80/8	4	1000	1-1/4"	FNR-1648-20			4-1/2"	12

18.4"	5.70/8	4	1170	1"		FNT-1857-16	4-1/2"	15
18.4"	5.70/8	4	1170	1-1/4"	FNR-1857-20		4-1/2"	15
21.0"	6.90/9	10	2420	1-1/4"		FNT-2169-20	7"	37.5
23.5"	6.50/10	10	2775	1-1/4"		FNT-2365-20	8"	38
25.7"	7.50/10	10	3630	1-1/4"		FNT-2575-20	9"	40