

Wheel Model Number System

Wheel Type	Wheel Bearing	Wheel Diameter	Wheel Width	Axle Dia. in 1/16" Increments	Options
UI	R	08	20	08	70D
CI-Cast Iron	B-Ball	03 - 3"	12 - 1-1/4"	05 - 5/16"	FF-Foam Filled*
DL-Durastan Laminated (Phenolic)	C-Celcon/Delrin	35 - 3-1/2"	15 - 1-1/2"	06 - 3/8"	HT-High Temp Lubrication
DU-Durastan (Phenolic)	O-Oilite	04 - 4"	20 - 2"	08 - 1/2"	LT-Low Temp Lubrication
FF-Machined Flanged Steel	P-Plain	05 - 5"	30 - 3"	10 - 5/8"	SS-Stainless Steel Spanner
FS-Forged Steel	R-Roller Straight	06 - 6"	40 - 4"	12 - 3/4"	SPBB-Sealed Precision Ball Bearing
FN-Full Pneumatic	T-Tapered Roller	08 - 8"	50 - 5"	16 - 1"	SSBB-Stainless SteelBall Bearing
GT-GT (Elastomer Blend)		10 - 10"	60 - 6"	20 - 1-1/4"	TG-Thread Guards*
HN-High Temp Nylon		12 - 12"			WS-Wheel Seals
HR-Hard Rubber (Solid)		14 - 14"			ZF-Zerk Fitting
MU-High Performance Solid Urethane		16 - 16"			70D-Optional Durometer*
NY-Nylatron HD		18 - 18"			80A-Optional Durometer*
PN-Pinnacle (Thermoplastic)		20 - 20"			90A-Optional Durometer*
PO-Polyolefin					
RA-Rubber on Aluminum					
RI-Rubber on Iron					
RP-Performance TPR					
SR-Soft Rubber (Solid)					
SW-Signature					
UA-Urethane on Aluminum					
UA-Torus					
UI-Urethane on Iron					
UO-Omega					
UP-Urethane on Polypropylene					
UT-Ultra Thick Urethane					
UW-Whisper					
VF-VGroove Forged Steel					
VI-VGroove Cast Iron					

* Certain Items Only