

The supreme performance benefits offered by the kingpinless caster design are available in both a locking plate design and a scaffold caster arrangement. Both casters offer significant improvements in shock load safety factor over conventional kingpin casters. Don't trust your life or goods to inadequate casters! Be sure you're using the strongest total lock and scaffolding casters on the market!

RWM Caster's new total lock design is centered around the versatile 65 series caster. These rigs offer more shock, thrust and towing load capacities to ensure safe and stable work environments. Perfect for use in the aerospace production industry where foreign object debris from failed kingpin type casters could spell disaster for work personnel or costly damaged components.

An excellent choice where work loads of heavy capacity tooling carts, composite molds or scaffolding must be 100% stationary, providing a stable and reliable work platform.



LS65-RIR-0820-S



LP65-RIR-0820-S

NEW!

SCAFFOLD (LOCKING STEM) 65 SERIES

Wheel Diameter	Wheel Width	Wheel Type	Capacity lbs.	Overall Height	Swivel Caster Model Number		Swivel Lead	Approx Weight lbs.
					Straight Roller Bearing	Ball Bearing		
8"	2"	Rubber on Iron	500	10-1/8"	LS65-RIR-0820-S	LS65-RIB-0820-S-Q	2-1/4"	

LOCKING PLATE 65 SERIES

Wheel Diameter	Wheel Width	Wheel Type	Capacity lbs.	Overall Height	Swivel Caster Model Number		Swivel Lead	Approx Weight lbs.
					Straight Roller Bearing	Ball Bearing		
8"	2"	Omega	1,200	10-1/2"	LP65-UOR-0820-S	LP65-UOB-0820-S	2-1/4"	
		Rubber on Iron	500		LP65-RIR-0820-S	LP65-RIB-0820-S-Q		
		Rubber on Aluminum EHT	750			LP65-RAB-0820-S-EHT		
		Signature	700		LP65-SWR-0820-S	LP65-SWB-0820-S		
		Torus	1,800			LP65-UAB-0821-S		
		Urethane on Aluminum	1,500		LP65-UAR-0820-S	LP65-UAB-0820-S-Q		
		Urethane on Iron	1,500		LP65-UIR-0820-S	LP65-UIB-0820-S-Q		

To order a rigid caster, change the "S" to "R" in the model number. For example: "65-CIR-0520-R". To order a rig only, omit the blue letters. For example: "65-0520-S". Dimensions shown are nominal. If precise dimensions are required, consult your RWM representative. For approximate weight of our rigid caster, deduct 1.5 pounds.