

RWM Soft Rubber wheels are manufactured of quality materials with a resilient rubber tread bonded to the hard rubber core. These wheels are an economical choice for moving equipment.



SRO-3512-06

## Applications

RWM Soft Rubber Wheels are a good choice for those applications where the average load is light with occasional loads using the full capacity of the wheel. Soft Rubber Wheels offer floor protection but can leave black marks on floors.

Soft Rubber Wheels wear on rough surfaces and can become brittle if left outdoors, exposed to the elements. Economical in smaller sizes, soft rubber wheels become more expensive in larger sizes, especially when premium rubber material is used.

## Options

- DC** Dust Cover
- TG** Thread Guards
- WS** Wheel Seals
- SI** Spanner Included

## Features

- Wheel Bearing:** Choice of straight roller bearing or oilite bearings
- Temperature Range:** -40°F to 120°F
- Durometer:** 70-75D

SPECIFICATIONS						
Wheel Diameter	Wheel Width	Capacity lbs.	Axle Diameter	Plain, Oilite, Celcon Bearing	Hub Length	Approx Weight
2-1/2"	1-1/10"	90	3/8"	SRO-2511-06	1-15/32"	0.5
3"	1-1/4"	250	5/16"	SRO-0312-05-SI	1-1/2"	0.8
			3/8"	SRO-0312-06		
3-1/2"	1-1/4"	250	5/16"	SRO-3512-05	1-1/2"	1.0
			3/8"	SRO-3512-06		
4"	1-1/4"	260	5/16"	SRO-0412-05	1-1/2"	1.2
			3/8"	SRO-0412-06		

UP TO 280 POUND CAPACITY