



1225 Isley Road, Gastonia, NC
28052
Phone: 800-634-7704 Fax:
800-253-6634
www.rwmcasters.com

RWM Signature Premium Wheel



The RWM Casters Signature™ Premium Wheel has a lightweight, reinforced nylon core with a high strength non-marking elastomeric rubber tread. The round tread provides easy rolling. Our durable nylon core is six times stronger than polypropylene. The performance rubber tread is cut, tear and corrosion resistant and will not chunk out. It has the highest strength-to-weight ratio than any other wheel in the industry. The Signature™ Premium Wheel is excellent for floor protection, continuous towing and noise reduction.



SWB-0820-08



SWB-0412-06

Features

Wheel Bearing: Choice of straight roller or precision ball bearing

Temperature Range: -40° to 200°F

Hardness: 70 Shore A

Bores: 1.190"

Applications

The RWM Signature™ Premium Wheel is ideal for:

- platform trucks
- material handling carts
- warehouse & factory applications
- food service
- drywall carts
- assembly line dollies

Specifications

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Straight Roller Bearing	Model	Hub Length	Approx Weight
3.5"	1.25"	225	3/8"		SWB-3512-06	1-5/8"	0.6
4"	1.25"	250	3/8"		SWB-0412-06	1-5/8"	0.7
4"	2"	400	1/2"	SWR-0420-08	SWB-0420-08	2-7/16"	1.3
5"	1.25"	250	3/8"		SWB-0512-06	1-5/8"	1
5"	2"	500	1/2"	SWR-0520-08	SWB-0520-08	2-7/16"	1.5
6"	1.25"	300	3/8"		SWB-0612-06	1-5/8"	1.5
6"	2"	600	1/2"	SWR-0620-08	SWB-0620-08	2-7/16"	2
8"	2"	700	1/2"	SWR-0820-08	SWB-0820-08	2-7/16"	2.8