

Solid Urethane Wheels

MU Wheels



The RWM Casters Solid Urethane Wheels offer quiet operation and rollability and are designed for towline applications such as automotive plants. This non-marking wheel is resistant to grease, oil, chemicals and moisture. In addition, it is also resistant to chunking, cutting and abrasive wear. These Solid Urethane Wheels are used in application that need lower noise levels, improved floor protection and where heavy loads and continuous use cause standard polyurethane wheels to heat up and degrade. These <u>Solid Urethane Wheels</u> are proudly Made in the USA.

The solid urethane wheels can be used for the following series of rigs to make durable, long-lasting casters: 46, 47, 48, 52, 65, 70, 75 and 76 Series.



MUB-0820-08

Features

Wheel Bearing: Available with Sealed Precision Ball Bearings only Temperature Range: -40°to +180°F Hub Length: Can be shortened or lengthened to order Hardness: MU wheel is 70 durometer Shore D

Applications

- automotive plants and towline applications
- applications needing lower noise levels
 applications needing improved floor protection
 applications where heavy loads and continuous use cause standard poly wheels to heat up and degrade

options

 ${\bf MU}$ High Performance Solid Urethane Wheel - color black ${\bf TG}$ Thread Guard on 2" wheels WSWheel Seals

Specifications

Wheel Diameter	₩heel Width	i lbs. Capacity	 Axle Diameter	D	Hub Length	 Approx Weight
4"	2"	700	1/2"	MUB-0420-08	2-3/16"	1.6
5"	2"	1000	1/2"	MUB-0520-08	2-3/16"	1.7
6"	2"	1200	1/2"	MUB-0620-08	2-3/16"	1.8
6"	3"	2000	3/4"	MUB-0630-12	3-1/2"	5
6"	3"	2000	1"	MUB-0630-16	3-1/2"	5

8"	2"	1500	1/2"	MUB-0820-08	2-7/16"	2.9
8"	3"	2500	3/4"	MUB-0830-12	3-1/2"	7
8"	3"	2500	1"	MUB-0830-16	3-1/2"	7
10"	3"	3000	3/4"	MUB-1030-12	3-1/2"	10
10"	3"	3000	1"	MUB-1030-16	3-1/2"	10