

Non-Marking EHT on Aluminum

RWM Elastomeric High Tensile Rubber Wheels are incredible molded rubber wheels. The high quality high tensile premium rubber is bonded to a heavy-duty solid web aluminum core that provides superior strength. These wheels are rated at 200% more than normal molded rubber wheels. This rubber wheel will not crack, chunk, dry out or debond. These elastomeric high tensile rubber wheels are excellent for towing applications in both indoor or outdoor environments. The special compound will not mark your floors. These rubber wheels can be used at higher rated towing speeds than other wheels. Please contact the factory for additional information.



RAB-0820-08-EHT-NM

Features

Hardness: 70-75 Shore A Durometer

Applications

RWM Elastomeric High Tensile Rubber Wheels provide excellent floor protection, are quiet and roll easily over debris. They will not mark floors. They are an excellent caster for large assembly plants, freight terminals, automotive plants, and continuous use operations.

SPECIFICATIONS

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Sealed Precision Ball Bearing	Tapered Roller Bearing	Hub Length	Approx Weight
4"	2"	700	1/2"	RAB-0420-08-EHT-NM		2-1/2"	1.6
			5/8"				
5"	2"	800	1/2"	RAB-0520-08-EHT-NM		2-1/2"	2.0
			5/8"				
6"	2"	820	1/2"	RAB-0620-08-EHT-NM		2-1/2"	2.7
			5/8"				
8"	2"	1000	1/2"	RAB-0820-08-EHT-NM		2-1/2"	3.7
			5/8"				
10"	3"	2000	3/4"	RAB-1030-12-EHT-NM	RAT-1030-12-EHT-NM	3-1/2"	10.0
			1"	RAB-1030-16-EHT-NM	RAT-1030-16-EHT-NM		
12"	3"	2280	3/4"	RAB-1230-12-EHT-NM	RAT-1230-12-EHT-NM	3-1/2"	14.5
			1"	RAB-1230-16-EHT-NM	RAT-1230-16-EHT-NM		
			1-1/4"		RAT-1230-20-EHT-NM		

UP TO 2,280 POUND CAPACITY