



1225 Isley Road, Gastonia, NC
28052
Phone: 800-634-7704 Fax:
800-253-6634
www.rwmcasters.com

Pinnacle Thermoplastic Wheels

PN Wheels



RWM Caster's **Pinnacle Thermoplastic Wheels** are ultra-tough glass filled nylon non-marking wheels. They are extremely durable, deflect floor debris and have high impact resistance. Our Pinnacle Thermoplastic Wheels roll easily and are able to handle high load capacities requiring far less force to roll than other hard tread wheels. This economical wheel is extremely resistant to water, most chemicals, solvents, salts and steam cleaning.

Our *Pinnacle Thermoplastic Wheels* are ideal for platform carts, material handling carts, warehouse and factory applications, food service and drywall carts.



Pinnacle Wheels

Features

Wheel Bearing: Choice of straight roller or celcon

Temperature Range: -40° to +350°F

Hardness: 85 D Shore Durometer

Specifications

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Straight Roller Bearing	Plain, Oilite, Celcon Bearing	Hub Length	Approx Weight
4"	2"	800	1/2"	PNR-0420-08	PNC-0420-08	2-7/16"	1.06
4"	2"	800	5/8"	PNR-0420-10	PNC-0420-10	2-7/16"	1.06
4"	2"	800	3/4"	PNR-0420-12	PNC-0420-12	2-7/16"	1.06
5"	2"	1000	1/2"	PNR-0520-08	PNC-0520-08	2-7/16"	1.27
5"	2"	1000	5/8"	PNR-0520-10	PNC-0520-10	2-7/16"	1.27
5"	2"	1000	3/4"	PNR-0520-12	PNC-0520-12	2-7/16"	1.27
6"	2"	1200	1/2"	PNR-0620-08	PNC-0620-08	2-7/16"	1.54
6"	2"	1200	5/8"	PNR-0620-10	PNC-0620-10	2-7/16"	1.54
6"	2"	1200	3/4"	PNR-0620-12	PNC-0620-12	2-7/16"	1.54
8"	2"	1400	1/2"	PNR-0820-08	PNC-0820-08	2-7/16"	2.1
8"	2"	1400	5/8"	PNR-0820-10	PNC-0820-10	2-7/16"	2.1
8"	2"	1400	3/4"	PNR-0820-12	PNC-0820-12	2-7/16"	2.1