



1225 Isley Road, Gastonia, NC 28052  
 Phone: 800-634-7704 Fax:  
 800-253-6634  
 www.rwmcasters.com

# Hard Rubber Wheels

HR Wheels



RWM Caster's Hard Rubber Wheels offer good floor protection, are more quiet than steel wheels, and are strong and chip resistant. These wheels have a center line located in the middle of the tread. This center line, even when removed as close as possible, can cause damage to soft inexpensive floors. Hard Rubber Wheels can become brittle over time, and more so when exposed to outdoor elements. **Hard Rubber Wheels** can crack when dropped from limited heights or subjected to impact or shock.



HRO-3512-06

## Features

**Wheel Bearing:** Oilite bearings  
**Temperature Range:** -30°F to 160°F

## Applications

RWM Caster's *Hard Rubber Wheels* are used where low cost, easy rolling wheels are required.

## options

**DC** Dust Cover  
**SI** Spanner Included

## Specifications

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Plain, Oilite, Calcon Bearing	Hub Length	Approx Weight
3"	1-1/4"	250	5/16"	HRO-0312-05-SI	1-1/2"	0.8
3"	1-1/4"	250	3/8"	HRO-0312-06	1-1/2"	0.8
3-1/2"	1-1/4"	250	5/16"	HRO-3512-05	1-1/2"	1
3-1/2"	1-1/4"	250	3/8"	HRO-3512-06	1-1/2"	1
4"	1-1/4"	260	5/16"	HRO-0412-05	1-1/2"	1.2
4"	1-1/4"	260	3/8"	HRO-0412-06	1-1/2"	1.2