

Hard Rubber wheels offer good floor protection, are more quiet than steel wheels, and are strong and chip resistant. These wheels have a center line located in the middle of the tread. This center line, even when removed as close as possible, can cause damage to soft inexpensive floors. Hard Rubber Wheels can become brittle over time, and more so when exposed to outdoor elements. Hard Rubber Wheels can crack when dropped from limited heights or subjected to impact or shock.



HRO-3512-06

Applications

RWM Hard Rubber Wheels are used where low cost, easy rolling wheels are required.

Options

- DC** Dust Cover
- SI** Spanner Included

Features

Wheel Bearing: Oilite bearings
Temperature Range: -30°F to 160°F
Durometer: 80-85D

SPECIFICATIONS

Wheel Diameter	Wheel Width	lbs.Capacity	Axle Diameter	Plain, Oilite, Celcon Bearing	Sealed Precision Ball Bearing	Hub Length	Approx Weight lbs.
2"	1"	175	5/16"		HRB-0210-05	1-1/2"	.03
2-1/2"	1-1/10"	100	3/8"	HRO-2511-06		1-15/32"	.05
3"	1-1/4"	150	5/16"	HRO-0312-05-SI		1-1/2"	0.7
			3/8"	HRO-0312-06			
3-1/2"	1-1/4"	150	5/16"	HRO-3512-05		1-1/2"	0.8
			3/8"	HRO-3512-06			
4"	1-1/4"	180	5/16"	HRO-0412-05		1-1/2"	1.1
			3/8"	HRO-0412-06			
4"	1-1/2"	200	1/2"	HRO-0415-08		1-7/8"	1.3
			5/8"	HRO-0415-10			
			3/4"				
5"	1-1/4"	200	5/16"	HRO-0512-05		1-1/2"	1.6
			3/8"	HRO-0512-06			

UP TO 200 POUND CAPACITY