



1225 Isley Road, Gastonia, NC 28052  
 Phone: 800-634-7704 Fax:  
 800-253-6634  
 www.rwmcasters.com

# Stainless Steel Wheel

RWM Casters Stainless Steel Wheels are well suited for highly corrosive environments and can be subjected to high temperatures without showing signs of degradation or corrosion. Produced in type 303 stainless steel these industrial wheels offer great capacity range and can withstand the most harmful environments when other wheels can't. [Click here](#) to view our latest flyer with updated specifications on this wheel.



SSP-0312-06

## Features

- **Bearing:** Choice of Plain bore, Celcon, Roller, and Sealed Ball Bearings
- **Temp Range:** Negative 30 to 600°\*
- **Fittings:** Lubrication fittings are not standard (Recommend the use of a zerked axle)
- **Material:** Type 303 Stainless Steel
- **Bores:** Bores may be altered and dimensions may be customized on most sizes
- **Options:** V-Groove & Flanged options available

\* Maximum temperature may be dependent on bearing choice. Sealed precision and Celcon bearings will have lower temp ranges.

## Applications

- Food Processing
- Clean Rooms
- Chemical Plants
- Autoclaves
- Medical
- Animal Cages

## Specifications

Wheel Diameter	Tread Face	Axle Diameter	Plain Bore	Celcon	Stainless Steel Roller Bearing	Stainless Steel Ball Bearing	lbs. Capacity	Hub Length	Approx Weight
3	1.25	3/8"	SSP-0312-06	SSC-0312-06		SSB-0312-06	450	1 1/2	3
3	1.25	1/2"	SSP-0312-08	SSC-0312-08			450	1 1/2	3
3	1.5	3/8"	SSP-0315-06	SSC-0315-06			500	1 7/8	3.25
3	1.5	1/2"	SSP-0315-08	SSC-0315-08			500	1 7/8	3.25
3.5	1.25	3/8"	SSP-3512-06	SSC-3512-06		SSB-3512-06	550	1 1/2	3.5
3.5	1.25	1/2"	SSP-3512-08	SSC-3512-08			550	1 1/2	3.5
3.5	1.5	3/8"	SSP-3515-06	SSC-3515-06			575	1 7/8	4
3.5	1.5	1/2"	SSP-3515-08	SSC-3515-08			575	1 7/8	4
4	1.25	3/8"	SSP-0412-06	SSC-0412-06		SSB-0412-06	650	1 1/2	4.5

4	1.25	1/2"	SSP-0412-08	SSC-0412-08			650	1 1/2	4.5
4	1.5	3/8"	SSP-0415-06	SSC-0415-06		SSB-0415-06	725	1 7/8	6
4	1.5	1/2"	SSP-0415-08	SSC-0415-08		SSB-0415-08	725	1 7/8	6
4	2	1/2"	SSP-0420-08	SSC-0420-08	SSR-0420-08	SSB-0420-08	900	2 7/16	8
4	2	5/8"	SSP-0420-10	SSC-0420-10	SSR-0420-10		900	2 7/16	8
4	2	3/4"	SSP-0420-12	SSC-0420-12	SSR-0420-12		900	2 7/16	8
5	1.5	3/8"	SSP-0515-06	SSC-0515-06		SSB-0515-06	800	1 7/8	9
5	1.5	1/2"	SSP-0515-08	SSC-0515-08		SSB-0515-08	800	1 7/8	9
5	2	1/2"	SSP-0520-08	SSC-0520-08	SSR-0520-08	SSB-0520-08	1000	2 7/16	12
5	2	5/8"	SSP-0520-10	SSC-0520-10	SSR-0520-10		1000	2 7/16	12
5	2	3/4"	SSP-0520-12	SSC-0520-12	SSR-0520-12		1000	2 7/16	12
6	1.5	3/8"	SSP-0615-06	SSC-0615-06		SSB-0615-06	900	1 7/8	11
6	1.5	1/2"	SSP-0615-08	SSC-0615-08		SSB-0615-08	900	1 7/8	11
6	2	1/2"	SSP-0620-08	SSC-0620-08	SSR-0620-08	SSB-0620-08	1100	2 7/16	19
6	2	5/8"	SSP-0620-10	SSC-0620-10	SSR-0620-10		1100	2 7/16	19
6	2	3/4"	SSP-0620-12	SSC-0620-12	SSR-0620-12		1100	2 7/16	19