

RWM Pneumatic Wheels provide smooth, shock-resistant operation for delicate instruments and breakable components. Pneumatic wheels are suggested for indoor and outdoor use where product protection is required. Pneumatic wheels offer the maximum in floor protection and move freely over obstructions and rough floors.



FNR-1648-20

## Applications

- ◆ Aerospace
- ◆ Tow-lines
- ◆ Automotive
- ◆ Boat Manufacturing
- ◆ Product Protection

## Options

- FF** Foam Filled
- WS** Wheel Seals
- ZF** Zerk Fitting

## Features

**Wheel Bearing:** Choice of straight roller, ball or tapered roller bearings.

**Operating Temperature Range:** -26 to 220°F

## SPECIFICATIONS

Wheel Diameter	Wheel Width	Ply Rating	lbs. Capacity	Axle Diameter	Straight Roller Bearing	Ball Bearing	Tapered Roller Bearing	Hub Length	lbs. Approx Weight
9.0"	2.80/4	4	300	1/2"	FNR-0828-08	FNB-0828-08		3-1/2"	4.5
				3/4"	FNR-0828-12	FNB-0828-12			
10.9"	4.10/4	4	480	1/2"	FNR-1041-08	FNB-1040-08		3-1/2"	5.5
				3/4"	FNR-1041-12		FNT-1041-12		
				1"	FNR-1041-16				
13.0"	4.10/6	4	500	3/4"	FNR-1241-12	FNB-1241-12	FNT-1241-12	4-1/2"	6.5
				1"	FNR-1241-16				
15.1"	5.30/6	4	870	3/4"	FNR-1448-12	FNB-1448-12		4-1/2"	9.0
				1"	FNR-1448-16				
16.3"	4.80/8	4	1000	1"	FNR-1648-16		FNT-1648-16	4-1/2"	12.0
				1-1/4"	FNR-1648-20				
18.4"	5.70/8	4	1170	1"			FNT-1857-16	4-1/2"	15.0
				1-1/4"	FNR-1857-20				
21.0"	6.90/9	10	2420	1-1/4"			FNT-2169-20	7"	37.5
23.5"	6.50/10	10	2775	1-1/4"			FNT-2365-20	8"	38.0
25.7"	7.50/10	10	3630	1-1/4"			FNT-2575-20	9"	40.0

Capacity rating is for manual operation. For capacities of power moved loads, please consult the factory. Full Pneumatic Wheels must be inflated as specified. For larger diameter, higher capacity pneumatic wheels, please consult the factory.