

Ultron Wheels

RWM's Nylatron HD Wheels are as strong as steel. These wheels are EXTREMELY heavy duty wheels designed for severe loads that won't sacrifice your floors! Nylatron HD Wheels do not chunk or separate under extreme applications. They are resilient against high temperature buildup from bearings and friction and will not chunk or separate. These wheels are a superb alternative to forged steel and other metal wheels.



NYB-0620-12

Features

- Temperature Range:** -40°F to +300°F
- Finish:** Machined Dark Gray
- Bores:** Special configurations and keyways available
- Keyways:** Can be installed on most sizes
- Bearings:** Sealed Precision Ball Bearings
- Durometer:** Shore 80-85D
- Options:** Flanged, V-Groove, and other configurations available upon request

Contact RWM for special sizes.

Hub length includes top hat bushings.

3" wide wheels require 4 precision ball bearings.

These wheels are not for use in heavily acidic or base environments.

There's no need to add an option for microbial resistance; through the use of superior polyurethane, RWM wheels are equipped to resist buildup from the factory.

SPECIFICATIONS

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Sealed Precision Ball Bearing	Hub Length	Approx Weight
2"	1"	250	5/16"	NYB-0210-05	1-1/6"	0.6
3"	1.25"	550	5/16"	NYB-0312-05	1-1/2"	1.2
			3/8"	NYB-0312-06		
3"	1.5"	700	3/8"	NYB-0315-06	1-7/8"	1.4
			1/2"	NYB-0315-08		
4"	1.25"	850	5/16"	NYB-0412-05	1-1/2"	1.8
			3/8"	NYB-0412-06		
4"	1.5"	1200	3/8"	NYB-0415-06	1-7/8"	2.1
			1/2"	NYB-0415-08		
4"	2"	2000	1/2"	NYB-0420-08	2-1/2"	2.5
			5/8"	NYB-0420-10		
		4000	3/4"	NYB-0420-12		
			1"	NYB-0420-16		
5"	1.25"	1200	5/16"	NYB-0512-05	1-1/2"	2.4
			3/8"	NYB-0512-06		
5"	1.5"	1400	3/8"	NYB-0515-06	1-7/8"	2.6
			1/2"	NYB-0515-08		
5"	2"	2000	1/2"	NYB-0520-08	2-1/2"	3
			5/8"	NYB-0520-10		
		4500	3/4"	NYB-0520-12		
			1"	NYB-0520-16		

UP TO 16,500 POUND CAPACITY

SPECIFICATIONS

Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Sealed Precision Ball Bearing	Hub Length	Approx Weight
6"	1.5"	1600	3/8"	NYB-0615-06	1-7/8"	3.4
			1/2"	NYB-0615-08		
6"	2"	2200	1/2"	NYB-0620-08	2-1/2"	4
			5/8"	NYB-0620-10		
		5000	3/4"	NYB-0620-12		
			1"	NYB-0620-16		
6"	2.5"	6500	3/4"	NYB-0625-16-YY	3"	4.5
			1"	NYB-0625-16-YY		
6"	3"	4000	1/2"	NYB-0630-08	3-1/2"	5.2
			5/8"	NYB-0630-10		
		10,000	3/4"	NYB-0630-12		
			1"	NYB-0630-16		
			1-1/4"	NYB-0630-20		
8"	2"	3000	1/2"	NYB-0820-08	2-1/2"	5.6
			5/8"	NYB-0820-10		
		5000	3/4"	NYB-0820-12		
			1"	NYB-0820-16		
8"	2.5"	7500	3/4"	NYB-0825-12-YY	3"	7.1
			1"	NYB-0825-16-YY		
8"	3"	10,000	3/4"	NYB-0830-12	3-1/2"	8
			1"	NYB-0830-16		
			1-1/4"	NYB-0830-20		
8"	4"	14,000	1"	NYB-0840-16	4-1/2"	12
			1-1/4"	NYB-0840-20		
10"	2.5	8500	3/4"	NYB-1025-12-YY	3"	9.5
			1"	NYB-1025-16-YY		
10"	3"	10,000	3/4"	NYB-1030-12	3-1/2"	11
			1"	NYB-1030-16		
			1-1/4"	NYB-1030-20		
10"	4"	16,500	1"	NYB-1040-16	4-1/2"	15
			1-1/4"	NYB-1040-20		
12"	3"	10,000	3/4"	NYB-1230-12	3-1/2"	13
			1"	NYB-1230-16		
			1-1/4"	NYB-1230-20		

UP TO 16,500 POUND CAPACITY