

Pinnacle Thermoplastic Wheels

PN Wheels

RWM's Pinnacle Wheel is an ultra-tough thermoplastic non-marking wheel. It is extremely durable, deflects floor debris and has high impact resistance. Pinnacle Glass Filled Nylon Wheels roll easily and are able to handle high load capacities requiring far less force to roll than other hard tread wheels. This economical wheel is extremely resistant to water, most chemicals, solvents, salts and steam cleaning. Pinnacle Nylon Wheels are available with roller bearings, oilite, celcon or plain bores and are standard black in color.



Applications

The RWM Pinnacle Wheels are ideal for:

- ◆ platform carts
- ◆ material handling carts
- ◆ warehouse & factory applications
- ◆ food service
- ◆ drywall carts

Features

Wheel Bearing: Choice of straight roller or celcon
Temperature Range: -40° to +350°F
Hardness: 85 D Shore Durometer

SPECIFICATIONS

Wheel Diameter	Wheel Width	Ibs.Capacity	Axle Diameter	Straight Roller Bearing	Plain, Oilite, Celcon Bearing	Hub Length	Approx Weight
4"	2"	800	1/2"	PNR-0420-08	PNC-0420-08	2-7/16"	1.06
			5/8"	PNR-0420-10	PNC-0420-10		
			3/4"	PNR-0420-12	PNC-0420-12		
5"	2"	1000	1/2"	PNR-0520-08	PNC-0520-08	2-7/16"	1.27
			5/8"	PNR-0520-10	PNC-0520-10		
			3/4"	PNR-0520-12	PNC-0520-12		
6"	2"	1200	1/2"	PNR-0620-08	PNC-0620-08	2-7/16"	1.54
			5/8"	PNR-0620-10	PNC-0620-10		
			3/4"	PNR-0620-12	PNC-0620-12		
8"	2"	1400	1/2"	PNR-0820-08	PNC-0820-08	2-7/16"	2.10
			5/8"	PNR-0820-10	PNC-0820-10		
			3/4"	PNR-0820-12	PNC-0820-12		

UP TO 1,400 POUND CAPACITY