

# Urethane on Aluminum Round Tread

The Torus Wheel™ offers a rounded tread that provides easy turning under heavy loads. The Torus Wheel™ features our premium **PTMEG** urethane tread, 92 on the Shore-A scale that is mechanically and chemically bonded to a light-weight sturdy aluminum core. This prevents tread separation and ensures maximum service life especially in demanding continuous use applications. The Torus Wheel™ has an aluminum core that provides a lightweight, long-lasting attractive alternative to cast iron.



UAB-0821-08



UAB-0821-08



UAB-0821-08

## Applications

The Torus Wheel™ is an exceptional wheel for continuous towline applications. It was developed specifically for automotive manufacturing assembly lines. This wheel offers excellent floor protection, noise reduction and is able to roll over small debris.

**\*Contact the factory for special automotive specific urethane wheel designs and options.**

### URETHANE WHEEL EXPERTS

RWM Casters has improved urethane compounds to withstand the new ergonomic, quality and value issues demanded in the aircraft, automotive and heavy-duty industrial material handling markets.

## Features

- Wheel Bearing:** Sealed precision bearing
- Temperature Range:** -40°F to 180°F
- Hardness:** Blue Wheel: 92 durometer shore A

There's no need to add an option for microbial resistance; through the use of superior polyurethane, RWM wheels are equipped to resist build-up from the factory.

SPECIFICATIONS						
Wheel Diameter	Wheel Width	lbs. Capacity	Axle Diameter	Sealed Precision Ball Bearing	Hub Length	Approx Weight
6"	2"	1230	1/2"	UAB-0621-08-92A	2-7/16"	3.1
8"	2"	1500	1/2"	UAB-0821-08-92A	2-7/16"	4.7



UP TO 1,500 POUND CAPACITY