

Mobile Printer

# MP-A40 Series



Measuring Instrument



PDA/Smart Device



Barcode



Portable Printer



Label



Medical Equipment



## High Reliability

- Drop rating: 2.0m(6.6feet) multiple
- IP rating: IP54
- Operating temperature: -20°C to 50°C

## Wide variety of driver and SDK for mobile equipment

## Simple operation

## Stylish design

Tough & Stylish Mobile Printer  
**MP-A40**  
 SERIES

Model	MP-A40
Method	Thermal line dot printing
Number of dots/line	832
Resolution (dots/mm)	8
Paper width (mm)	80 <sup>+0</sup> / <sub>-1</sub> / 100 <sup>+0</sup> / <sub>-1</sub> / 105 <sup>+0</sup> / <sub>-1</sub> / 112 <sup>+0</sup> / <sub>-1</sub>
Printing width (mm)	104
Speed (mm/sec) max	105
Outside diameter of paper roll (mm) max	Φ58
Character matrix (HxW mm)	24 x 12, 24 x 24, 16 x 8, 16 x 16
Character dimensions (HxW mm)	3.0 x 1.5, 3.0 x 3.0, 2.0 x 1.0, 2.0 x 2.0
Type of paper	Roll paper, Label roll paper
Character type	Code page : 17pages, Katakana character, Option font, Downloaded character, User-defined character, JIS 1 & 2 level kanji
Bar code	UPC-A/E, JAN(EAN)8/13, ITF, CODE39, CODABAR, CODE93, CODE128, PDF417, QR Code, MaxiCode, Data Matrix, GS1 Databar
Power supply(v)	Option : Specified AC adapter, Li-Ion battery
Communication interface	USB, Bluetooth®, WLAN <sup>*1</sup>
Input buffer	4K bytes
Command	ESC/POS™ conformity, CPCL conformity, Markup Language
Cutting	Tea bar
Drop Rating	2.0m (6.6feet) multiple <sup>*2</sup>
IP rating	IP54 <sup>*2</sup>
Operating temperature (°C)	-20 to 50
Service life (km)	50 <sup>*3</sup>
Dimensions (WxDxH mm)	156 x 152 x 71 <sup>*4</sup>
Mass (g)	Approx. 760 <sup>*5</sup>
Standard	FCC, CE, VCCI
Option	AC adapter, Battery pack, Battery charger(single/quad), AC cable, USB cable, Serial cable, Car charger, Strap
Software	Printer driver, Windows® CE(SDK), Android™(SDK), iOS

\*1 Selected model. \*2 test performance by specified condition. \*3 Use recommended thermal papers. \*4 Excluding protrusion \*5 Including battery, excluding roll paper

ESC/POS™ is a registered trademark of SEIKO EPSON Corporation.  
 Windows® is a registered trademark of Microsoft Corporation(USA).  
 Android™ is a trade mark of Google Inc.

Specifications are subject to change without notice.

# SII

Seiko Instruments Inc.

Print System Div.

8, Nakase 1-chome, Mihama-ku  
 Chiba-shi, Chiba 261-8507, Japan

Telephone:+81-43-211-1106 Facsimile:+81-43-211-8037

Seiko Instruments USA Inc.

2990 Lomita Blvd., Torrance, CA 90505, USA.  
 Telephone:+1-310-517-7778 Facsimile:+1-310-517-8154

Seiko Instruments GmbH

Siemensstrasse 9 D-63263 Neu-Isenburg, Germany  
 Telephone:+49-6102-297-0 Facsimile:+49-6102-297-222  
 E-mail : info@seiko-instruments.de

Seiko Instruments (H.K.) Ltd.

4-5 / F, Wyler Center 2, 200 Tai Lin Pai Road, Kwai Chung,  
 N.T., Kowloon, Hong Kong  
 Telephone:+852-2494-5160 Facsimile:+852-2424-0901

Seiko Instruments Taiwan Inc.

6F, No.236, Sec.2, Jianguo N.Rd., Taipei 104, Taiwan, R.O.C.  
 Telephone:+886-2-2516-8518 Facsimile:+886-2-2516-1186



Printed in Mar. 2016

1-0323-0/KO/PS Printed in Japan

Homepage <http://www.sii-ps.com>