



Surface Mount SMA & SMB Low Vf Schottkys

Friday, 2 March 2012

Sirectifier Global Corp. (SGC) announced that the package of SMA & SMB surface-mount SBD for the high-efficiency portable and SMPS applications.

The lowest forward-drop Voltage(Vf) of these between 0.35V and 0.40V at the temperature of 125°C. The followings are the already provided item at present:

SMA Type-

SSR2L4 2A/40V

SSR2L6 2A/60V

SSR3L4 3A/40V

SSR3L6 3A/60V



SMA/ DO-214AC

SMB Type-

SBR3L4 3A/40V

SBR3L6 3A/60V



SMB/ DO214AA

For further details, please contact SGC at the location nearest you.

Sales Representatives:

U.S.A. -

113 Barksdale Professional
Center in the City of Newark,
County of New Castle, Delaware
e-mail: sgc@sirectsemi.com

China -

Room 302, Block A, Nanfangguoji
Plaza, Yitian Rd. 3013, Futian
district, Shenzhen, China
e-mail: candy@sirectifier.com.tw

Taiwan -

19F-3, NO. 75, Sec. 1, Xintai
5th Rd., Xixhi City, Taipei, Taiwan
e-mail: se@sirectsemi.com

Thailand -

29/123 F.8 Siam Condo. Rama 9
Rd., Huaykwang, Bangkok
10310, Thailand
e-mail: th@sirectsemi.com